




# OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id  
**KAESER 6335245**  
 Component  
**Compressor**  
 Fluid  
**KAESER SIGMA (OEM) S-460 (--- GAL)**

## DIAGNOSIS

**Recommendation**  
 Resample at the next service interval to monitor.

**Wear**  
 All component wear rates are normal.

**Contamination**  
 The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.

**Fluid Condition**  
 The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>KC111677</b>	KC96443	KC67387
Sample Date	Client Info		<b>06 Jun 2023</b>	16 Dec 2021	14 Aug 2019
Machine Age	hrs	Client Info	<b>25792</b>	19623	5430
Oil Age	hrs	Client Info	<b>0</b>	2026	2967
Oil Changed	Client Info		<b>Changed</b>	Not Changd	Not Changd
Sample Status			<b>NORMAL</b>	ABNORMAL	ABNORMAL

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >50	<b>&lt;1</b>	2	1
Chromium	ppm	ASTM D5185m >10	<b>0</b>	0	0
Nickel	ppm	ASTM D5185m >3	<b>0</b>	0	0
Titanium	ppm	ASTM D5185m >3	<b>0</b>	0	0
Silver	ppm	ASTM D5185m >2	<b>0</b>	<1	0
Aluminum	ppm	ASTM D5185m >10	<b>0</b>	0	<1
Lead	ppm	ASTM D5185m >10	<b>0</b>	0	<1
Copper	ppm	ASTM D5185m >50	<b>3</b>	5	16
Tin	ppm	ASTM D5185m >10	<b>0</b>	<1	0
Antimony	ppm	ASTM D5185m	<b>---</b>	0	0
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	<b>0</b>	25	0
Barium	ppm	ASTM D5185m 90	<b>11</b>	0	11
Molybdenum	ppm	ASTM D5185m	<b>0</b>	0	0
Manganese	ppm	ASTM D5185m	<b>0</b>	<1	0
Magnesium	ppm	ASTM D5185m 90	<b>61</b>	74	74
Calcium	ppm	ASTM D5185m 2	<b>3</b>	2	1
Phosphorus	ppm	ASTM D5185m	<b>1</b>	3	4
Zinc	ppm	ASTM D5185m	<b>22</b>	32	4

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>&lt;1</b>	<1	2
Sodium	ppm	ASTM D5185m	<b>23</b>	26	19
Potassium	ppm	ASTM D5185m >20	<b>2</b>	3	3
Water	%	ASTM D6304 >0.05	<b>0.015</b>	0.008	0.027
ppm Water	ppm	ASTM D6304 >500	<b>157.1</b>	85.6	270.8






## FLUID CLEANLINESS

	method	limit/base	current	history1	history2
Particles >4µm	ASTM D7647		<b>1323</b>	15363	30595
Particles >6µm	ASTM D7647 >1300		<b>372</b>	▲ 4385	▲ 6077
Particles >14µm	ASTM D7647 >80		<b>36</b>	▲ 229	▲ 81
Particles >21µm	ASTM D7647 >20		<b>13</b>	▲ 42	15
Particles >38µm	ASTM D7647 >4		<b>1</b>	4	3
Particles >71µm	ASTM D7647 >3		<b>0</b>	0	0
Oil Cleanliness	ISO 4406 (c) >--/17/13		<b>18/16/12</b>	▲ 19/15	▲ 20/14

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045 0.4	<b>0.36</b>	0.37	0.313


# OIL ANALYSIS REPORT








VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	LIGHT	LIGHT
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445 46	44.4	44.0	42.3

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------



## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : KC111677 **Received** : 24 Aug 2023  
**Lab Number** : 05933627 **Diagnosed** : 25 Aug 2023  
**Unique Number** : 10618898 **Diagnostician** : Don Baldrige  
**Test Package** : IND 2

**MATICK AUTO GROUP**  
 13955 TELEGRAPH RD  
 REDFORD, MI  
 US 48239  
 Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: