




OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id
7947111 (S/N 1164)
 Component
Compressor
 Fluid
KAESER SIGMA (OEM) S-460 (--- GAL)

DIAGNOSIS

Recommendation
 Resample at the next service interval to monitor.

Wear
 All component wear rates are normal.

Contamination
 The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.

Fluid Condition
 The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	KC102371	KC97295	---
Sample Date	Client Info	01 May 2023	11 Apr 2022	---
Machine Age	hrs Client Info	15003	5776	---
Oil Age	hrs Client Info	6000	3000	---
Oil Changed	Client Info	Changed	Not Changd	---
Sample Status		NORMAL	ABNORMAL	---

WEAR METALS

method	limit/base	current	history1	history2
Iron ppm ASTM D5185m	>50	<1	<1	---
Chromium ppm ASTM D5185m	>10	0	0	---
Nickel ppm ASTM D5185m	>3	0	<1	---
Titanium ppm ASTM D5185m	>3	0	0	---
Silver ppm ASTM D5185m	>2	0	0	---
Aluminum ppm ASTM D5185m	>10	0	<1	---
Lead ppm ASTM D5185m	>10	0	0	---
Copper ppm ASTM D5185m	>50	7	3	---
Tin ppm ASTM D5185m	>10	0	<1	---
Vanadium ppm ASTM D5185m		0	0	---
Cadmium ppm ASTM D5185m		0	0	---

ADDITIVES

method	limit/base	current	history1	history2
Boron ppm ASTM D5185m		0	<1	---
Barium ppm ASTM D5185m	90	0	0	---
Molybdenum ppm ASTM D5185m		0	0	---
Manganese ppm ASTM D5185m		0	0	---
Magnesium ppm ASTM D5185m	90	<1	20	---
Calcium ppm ASTM D5185m	2	2	0	---
Phosphorus ppm ASTM D5185m		1	4	---
Zinc ppm ASTM D5185m		0	12	---

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon ppm ASTM D5185m	>25	0	2	---
Sodium ppm ASTM D5185m		0	<1	---
Potassium ppm ASTM D5185m	>20	0	0	---
Water % ASTM D6304	>0.05	0.004	0.015	---
ppm Water ppm ASTM D6304	>500	43.1	157.6	---






FLUID CLEANLINESS

method	limit/base	current	history1	history2
Particles >4µm ASTM D7647		5598	10657	---
Particles >6µm ASTM D7647	>1300	1282	▲ 2609	---
Particles >14µm ASTM D7647	>80	64	▲ 114	---
Particles >21µm ASTM D7647	>20	17	▲ 25	---
Particles >38µm ASTM D7647	>4	1	1	---
Particles >71µm ASTM D7647	>3	0	0	---
Oil Cleanliness ISO 4406 (c)	>--/17/13	20/17/13	▲ 21/19/14	---

FLUID DEGRADATION

method	limit/base	current	history1	history2
Acid Number (AN) mg KOH/g ASTM D8045	0.4	0.45	0.37	---


OIL ANALYSIS REPORT








VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	LIGHT	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.05	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	46	44.8	43.9

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------



GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : KC102371 **Received** : 24 Aug 2023
Lab Number : 05933629 **Diagnosed** : 25 Aug 2023
Unique Number : 10618900 **Diagnostician** : Don Baldrige
Test Package : IND 2

INTERNATIONAL EXTRUSIONS
 39001 SCHOOLCRAFT RD
 LIVONIA, MI
 US 48150
 Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: