

Component Compressor

#### **PROBLEM SUMMARY**

KAESER AS 25 5950570 - CUSTOMER NOT PROVIDED (S/N 1261)

## Sample Rating Trend VIS DEBRIS

No relevant graphs to display

#### RECOMMENDATION

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.

KAESER SIGMA (OEM) S-460 (--- GAL)

COMPONENT CONDITION SUMMARY

| PROBLEMATIC T | EST RE | SULTS   |      |          |      |
|---------------|--------|---------|------|----------|------|
| Sample Status |        |         |      | ABNORMAL | <br> |
| Debris        | scalar | *Visual | NONE |          | <br> |

Customer Id: KAEFRE Sample No.: KC111736 Lab Number: 05933632 Test Package: IND 2



To manage this report scan the QR code

To discuss the diagnosis or test data: Don Baldridge +1 don.b505@comcast.net

To change component or sample information: Customer Service +1 1-800-237-1369 customerservice@wearcheck.com

| RECOMMENDE | ED ACTIONS |      |         |   |
|------------|------------|------|---------|---|
| Action     | Status     | Date | Done By | Description   |
| Alert      |            |      | ?       | We were unable to perform a particle count due to a high concentration of particles present in this sample. |

HISTORICAL DIAGNOSIS



#### **OIL ANALYSIS REPORT**

# VIS DEBRIS

Sample Rating Trend

### KAESER AS 25 5950570 - CUSTOMER NOT PROVIDED (S/N 1261)

Compressor Fluid

KAESER SIGMA (OEM) S-460 (--- GAL)

#### DIAGNOSIS

#### Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.

#### Wear

All component wear rates are normal.

#### Contamination

Moderate concentration of visible dirt/debris present in the oil.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

| Iron         ppm         ASTM D5185m         >50         <1   | story2  |
|---|---------|
| Sample Date         Client Info         18 Apr 2023             Machine Age         hrs         Client Info         6508             Oil Age         hrs         Client Info         1500             Oil Changed         Client Info         Not Changd              Sample Status         Imathy         Client Info         Not Changd             VEAR METALS         method         Imithy         ABNORMAL              Nickel         ppm         ASTM D5185m         >50         <1   | story2  |
| Machine Age         hrs         Client Info         6508             Oil Age         hrs         Client Info         1500              Oil Changed         Client Info         Not Changd   | story2  |
| Oil Age         hrs         Client Info         1500             Oil Changed         Client Info         Not Changd              Sample Status         Imation         Pmethod         Iimit/base         current         history1            WEAR METALS         method         Iimit/base         current         history1             Iron         ppm         ASTM D5185m         >50         <1  | story2  |
| Not Changed       Client Info       Not Changed   | story2  |
| Sample Status         Image Method         Imit/base         Current         history1         nm           Iron         ppm         ASTM D5185m         >50         <1  | istory2 |
| Iron         ppm         ASTM D5185m         >50         <1             Chromium         ppm         ASTM D5185m         >10         0             Nickel         ppm         ASTM D5185m         >3         0             Titanium         ppm         ASTM D5185m         >3         0             Silver         ppm         ASTM D5185m         >2         0             Aluminum         ppm         ASTM D5185m         >10         0             Lead         ppm         ASTM D5185m         >10         0             Copper         ppm         ASTM D5185m         >10         0             Vanadium         ppm         ASTM D5185m         >10         0  | istory2 |
| Chromium         ppm         ASTM D5185m         >10         0             Nickel         ppm         ASTM D5185m         >3         0             Titanium         ppm         ASTM D5185m         >3         0             Silver         ppm         ASTM D5185m         >2         0             Aluminum         ppm         ASTM D5185m         >10         0             Lead         ppm         ASTM D5185m         >10         0             Copper         ppm         ASTM D5185m         >10         0   |         |
| Chromium         ppm         ASTM D5185m         >10         0             Nickel         ppm         ASTM D5185m         >3         0             Titanium         ppm         ASTM D5185m         >3         0             Silver         ppm         ASTM D5185m         >2         0             Aluminum         ppm         ASTM D5185m         >10         0             Lead         ppm         ASTM D5185m         >10         0             Copper         ppm         ASTM D5185m         >10         0             Vanadium         ppm         ASTM D5185m         >10         0             Vanadium         ppm         ASTM D5185m         0   |         |
| Titanium         ppm         ASTM D5185m         >3         0             Silver         ppm         ASTM D5185m         >2         0             Aluminum         ppm         ASTM D5185m         >10         0             Lead         ppm         ASTM D5185m         >10         0             Copper         ppm         ASTM D5185m         >50         22             Tin         ppm         ASTM D5185m         >10         0             Vanadium         ppm         ASTM D5185m         >10         0             Cadmium         ppm         ASTM D5185m         0              ADDITIVES         method         limit/base         current         history1         h           Boron         ppm         ASTM D5185m         90         2             Molybdenum         ppm         ASTM D5185m         0              Magnesium         ppm         ASTM D5185m   |         |
| Titanium         ppm         ASTM D5185m         >3         0             Silver         ppm         ASTM D5185m         >2         0             Aluminum         ppm         ASTM D5185m         >10         0             Lead         ppm         ASTM D5185m         >10         0             Copper         ppm         ASTM D5185m         >50         22             Tin         ppm         ASTM D5185m         >10         0             Vanadium         ppm         ASTM D5185m         >10         0             Cadmium         ppm         ASTM D5185m         >10         0             ADDITIVES         method         limit/base         current         history1         h           Boron         ppm         ASTM D5185m         90         2             Molybdenum         ppm         ASTM D5185m         90         477             Magnesium         ppm         ASTM D5185m         2<   |         |
| Silver       ppm       ASTM D5185m       >2       0           Aluminum       ppm       ASTM D5185m       >10       0           Lead       ppm       ASTM D5185m       >10       0           Copper       ppm       ASTM D5185m       >50       22           Tin       ppm       ASTM D5185m       >10       0           Vanadium       ppm       ASTM D5185m       >10       0           Vanadium       ppm       ASTM D5185m       >10       0           Cadmium       ppm       ASTM D5185m       0            ADDITIVES       method       limit/base       current       history1       h         Boron       ppm       ASTM D5185m       90       2           Molybdenum       ppm       ASTM D5185m       90       477           Magnesium       ppm       ASTM D5185m       2       2  |         |
| Aluminum         ppm         ASTM D5185m         >10         0             Lead         ppm         ASTM D5185m         >10         0             Copper         ppm         ASTM D5185m         >50         22             Tin         ppm         ASTM D5185m         >10         0             Vanadium         ppm         ASTM D5185m         >10         0             Cadmium         ppm         ASTM D5185m         >10         0             ADDITIVES         method         limit/base         current         history1         h           Boron         ppm         ASTM D5185m         90         2             Molybdenum         ppm         ASTM D5185m         90         2             Maganesium         ppm         ASTM D5185m         90         47             Magnesium         ppm         ASTM D5185m         2         2             Contaduim         ppm         ASTM D5185m   |         |
| Lead         ppm         ASTM D5185m         >10         0             Copper         ppm         ASTM D5185m         >50         22             Tin         ppm         ASTM D5185m         >10         0             Vanadium         ppm         ASTM D5185m         >10         0             Cadmium         ppm         ASTM D5185m         Imit/base         Current         history1         h           ADDITIVES         method         limit/base         current         history1         h           Boron         ppm         ASTM D5185m         90         2             Molybdenum         ppm         ASTM D5185m         90         2             Maganese         ppm         ASTM D5185m         90         477             Magnesium         ppm         ASTM D5185m         2         2             Phosphorus         ppm         ASTM D5185m         2         2   |         |
| Copper         ppm         ASTM D5185m         >50         22             Tin         ppm         ASTM D5185m         >10         0             Vanadium         ppm         ASTM D5185m         >10         0             Cadmium         ppm         ASTM D5185m         Imit/base         Current         history1         h           ADDITIVES         method         limit/base         current         history1         h           Boron         ppm         ASTM D5185m         90         2             Molybdenum         ppm         ASTM D5185m         90         2             Manganese         ppm         ASTM D5185m         90         477             Magnesium         ppm         ASTM D5185m         2         2             Phosphorus         ppm         ASTM D5185m         2         2             CONTAMINANTS         method         limit/base         current         history1         h           Silicon         ppm         ASTM D5185m   |         |
| Tin         ppm         ASTM D5185m         >10         0             Vanadium         ppm         ASTM D5185m         Ica         0          Ica         Ica |         |
| Vanadium         ppm         ASTM D5185m         0          Cadmium         ppm         ASTM D5185m         0          Cadmium         ppm         ASTM D5185m         0          Cadmium         ppm         ASTM D5185m         0             ADDITIVES         method         limit/base         current         history1         h           Boron         ppm         ASTM D5185m         90         2             Barium         ppm         ASTM D5185m         90         2             Molybdenum         ppm         ASTM D5185m         90         2             Manganese         ppm         ASTM D5185m         90         477             Magnesium         ppm         ASTM D5185m         2         2             Calcium         ppm         ASTM D5185m         2         2             Zinc         ppm         ASTM D5185m         2         0   |         |
| CadmiumppmASTM D5185m0ADDITIVESmethodlimit/basecurrenthistory1hBoronppmASTM D5185m0BariumppmASTM D5185m902MolybdenumppmASTM D5185m902ManganeseppmASTM D5185m0MagnesiumppmASTM D5185m9047CalciumppmASTM D5185m22PhosphorusppmASTM D5185m22ZincppmASTM D5185m20SiliconppmASTM D5185m>250SodiumppmASTM D5185m>201PotassiumppmASTM D5185m>201   |         |
| Boron         ppm         ASTM D5185m         0             Barium         ppm         ASTM D5185m         90         2             Molybdenum         ppm         ASTM D5185m         90         2             Manganese         ppm         ASTM D5185m         0             Magnesium         ppm         ASTM D5185m         90         47             Calcium         ppm         ASTM D5185m         2         2             Phosphorus         ppm         ASTM D5185m         2         2             Zinc         ppm         ASTM D5185m         2         40             Silicon         ppm         ASTM D5185m         >25         0             Sodium         ppm         ASTM D5185m         >25         0             Potassium         ppm         ASTM D5185m         >20         1   |         |
| Barium         ppm         ASTM D5185m         90         2          4           Molybdenum         ppm         ASTM D5185m         0              Manganese         ppm         ASTM D5185m         0             Magnesium         ppm         ASTM D5185m         90         47             Calcium         ppm         ASTM D5185m         2         2             Phosphorus         ppm         ASTM D5185m         2         2             Zinc         ppm         ASTM D5185m         2         40             Solicon         ppm         ASTM D5185m         >25         0             Sodium         ppm         ASTM D5185m         >25         0             Potassium         ppm         ASTM D5185m         >20         1  | istory2 |
| Barium         ppm         ASTM D5185m         90         2          4           Molybdenum         ppm         ASTM D5185m         0              Manganese         ppm         ASTM D5185m         0             Magnesium         ppm         ASTM D5185m         90         47             Calcium         ppm         ASTM D5185m         2         2             Phosphorus         ppm         ASTM D5185m         2         2             Zinc         ppm         ASTM D5185m         2         40             CONTAMINANTS         method         limit/base         current         history1         h           Silicon         ppm         ASTM D5185m         >25         0             Sodium         ppm         ASTM D5185m         >20         1  | -       |
| Molybdenum         ppm         ASTM D5185m         0             Manganese         ppm         ASTM D5185m         90         47             Magnesium         ppm         ASTM D5185m         90         47             Calcium         ppm         ASTM D5185m         2         2             Phosphorus         ppm         ASTM D5185m         2         2             Zinc         ppm         ASTM D5185m         2         40             CONTAMINANTS         method         limit/base         current         history1         h           Silicon         ppm         ASTM D5185m         >25         0             Sodium         ppm         ASTM D5185m         >20         1  |         |
| Manganese         ppm         ASTM D5185m         0             Magnesium         ppm         ASTM D5185m         90         47             Calcium         ppm         ASTM D5185m         2         2             Phosphorus         ppm         ASTM D5185m         2         2             Zinc         ppm         ASTM D5185m         40             CONTAMINANTS         method         limit/base         current         history1         h           Silicon         ppm         ASTM D5185m         >25         0             Sodium         ppm         ASTM D5185m         >20         1   |         |
| Magnesium         ppm         ASTM D5185m         90         47             Calcium         ppm         ASTM D5185m         2         2             Phosphorus         ppm         ASTM D5185m         2         2             Zinc         ppm         ASTM D5185m         40             CONTAMINANTS         method         limit/base         current         history1         h           Silicon         ppm         ASTM D5185m         >25         0             Sodium         ppm         ASTM D5185m         >20         1   |         |
| Calcium         ppm         ASTM D5185m         2         2             Phosphorus         ppm         ASTM D5185m         2              Zinc         ppm         ASTM D5185m         2         40             CONTAMINANTS         method         limit/base         current         history1         h           Silicon         ppm         ASTM D5185m         >25         0             Sodium         ppm         ASTM D5185m         >20         1  |         |
| Phosphorus         ppm         ASTM D5185m         2             Zinc         ppm         ASTM D5185m         40              CONTAMINANTS         method         limit/base         current         history1         h           Silicon         ppm         ASTM D5185m         >25         0             Sodium         ppm         ASTM D5185m         >20         1  |         |
| Zinc         ppm         ASTM D5185m         40             CONTAMINANTS         method         limit/base         current         history1         h           Silicon         ppm         ASTM D5185m         >25         0             Sodium         ppm         ASTM D5185m         >20         1  |         |
| CONTAMINANTSmethodlimit/basecurrenthistory1hSiliconppmASTM D5185m>250SodiumppmASTM D5185m21PotassiumppmASTM D5185m>201  |         |
| Silicon         ppm         ASTM D5185m         >25         0             Sodium         ppm         ASTM D5185m         21             Potassium         ppm         ASTM D5185m         >20         1   |         |
| Sodium         ppm         ASTM D5185m         21             Potassium         ppm         ASTM D5185m         >20         1   | story2  |
| Potassium         ppm         ASTM D5185m         >20         1   |         |
|   |         |
| Water % ASTM 06304 >0.05 0.017  |         |
|   |         |
| ppm Water ppm ASTM D6304 >500 <b>179.0</b>  |         |
| FLUID DEGRADATION method limit/base current history1 h  | istory2 |
| Acid Number (AN) mg KOH/g ASTM D8045 0.4 0.39   |         |
| VISUAL method limit/base current history1 h   | story2  |
| White Metal         scalar         *Visual         NONE         NONE  |         |
| Yellow Metal scalar *Visual NONE NONE   |         |
| Precipitate scalar *Visual NONE NONE  |         |
| Silt scalar *Visual NONE NONE   |         |
| Debris scalar *Visual NONE A MODER  |         |
| Sand/Dirt scalar *Visual NONE NONE  |         |
| Appearance scalar *Visual NORML NORML   |         |
| Odor scalar *Visual NORML NORML   |         |
| Emulsified Water scalar *Visual >0.05 NEG   |         |
| Free Water scalar *Visual NEG Varranty Department-  |         |



**OIL ANALYSIS REPORT** 



Contact/Location: Warranty Department - KAEFRE