

# **OIL ANALYSIS REPORT**

### Sample Rating Trend

# NORMAL



# Grand Blanc CAT 7 GBLM07BE

**Biogas Engine** 

CHEVRON HDAX 6500 LFG GAS ENGINE OIL (--- GAL)

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil


#### **Fluid Condition**


The BN result indicates that there is suitable alkalinity remaining in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


GAS ENGINE OIL (	GAL)	g2022 Oct20				
SAMPLE INFORM	/ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC05934953	WC0825012	WC0824957
Sample Date		Client Info		24 Aug 2023	13 Aug 2023	02 Aug 2023
Machine Age	hrs	Client Info		124841	124531	124341
Oil Age	hrs	Client Info		0	0	592
Oil Changed		Client Info		N/A	N/A	Not Changd
Sample Status				NORMAL	ABNORMAL	NORMAL
CONTAMINATIO	V	method	limit/base	current	history1	history2
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Glycol		WC Method		NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>15	2	4	2
Chromium	ppm	ASTM D5185m	>4	<1	0	0
Nickel	ppm	ASTM D5185m	>2	0	0	0
Titanium	ppm	ASTM D5185m		0	<1	<1
Silver	ppm	ASTM D5185m	>5	0	0	0
Aluminum	ppm	ASTM D5185m	>6	2	1	2
Lead	ppm	ASTM D5185m	>9	<1	<1	2
Copper	ppm	ASTM D5185m	>6	<1	2	2
Tin	ppm	ASTM D5185m	>4	1	2	2
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		1	<1	1
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		8	9	12
Calcium	ppm	ASTM D5185m		2169	1996	1873
Phosphorus	ppm	ASTM D5185m		316	286	271
Zinc	ppm	ASTM D5185m		388	343	331
Sulfur	ppm	ASTM D5185m		3685	4008	3650
CONTAMINANTS	;	method	12 25 0			0. سواروا
		memou	limit/base	current	history1	nistoryz
Silicon	ppm	ASTM D5185m	>181	current <b>75</b>	history1 139	113
Silicon Sodium						
Silicon Sodium Potassium	ppm	ASTM D5185m	>181	75	139	113
Sodium	ppm	ASTM D5185m ASTM D5185m	>181	75 0	139	113 2 <1
Sodium Potassium	ppm	ASTM D5185m ASTM D5185m ASTM D5185m	>181	75 0 2	139 2 <1	113 2 <1
Sodium Potassium INFRA-RED Soot %	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m method	>181	75 0 2 current	139 2 <1 history1	113 2 <1 history2
Sodium Potassium INFRA-RED Soot %	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D7844	>181 >20 limit/base	75 0 2 current	139 2 <1 history1	113 2 <1 history2
Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm % Abs/cm Abs/.1mm	ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D7844 *ASTM D7624	>181 >20 limit/base >20	75 0 2 current 0 5.5	139 2 <1 history1 0.1 6.0	113 2 <1 history2 0 6.1 25.1
Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm % Abs/cm Abs/.1mm	ASTM D5185m ASTM D5185m ASTM D5185m method *ASTM D7844 *ASTM D7624 *ASTM D7415	>181 >20 limit/base >20 >30	75 0 2 current 0 5.5 19.7	139 2 <1 history1 0.1 6.0 26.2	113 2 <1 history2 0 6.1 25.1
Sodium Potassium INFRA-RED Soot % Nitration Sulfation FLUID DEGRADA	ppm ppm ppm % Abs/cm Abs/.1mm	ASTM D5185m ASTM D5185m ASTM D5185m  method  *ASTM D7844  *ASTM D7624  *ASTM D7415  method  *ASTM D7414	>181 >20 limit/base >20 >30 limit/base	75 0 2 current 0 5.5 19.7	139 2 <1 history1 0.1 6.0 26.2 history1	2 <1 history2 0 6.1 25.1 history2



## **OIL ANALYSIS REPORT**










VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
<b>Emulsified Water</b>	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


LLUID PHOPER	THES	method			riistory i	History
Visc @ 100°C	cSt	ASTM D445	14.7	13.5	14.0	13.8


	1	~1	$\overline{}$	V	7^
22	23	73	73	73	23
Nov29,	Jan11	Marl	Apr10	Иау22.	Jul19/23
	Nov29/22	Muv29/22			





















Certificate L2367

Laboratory Sample No. Lab Number **Unique Number** Test Package : MOB 2

: WC05934953 : 05934953

: 10620224

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 25 Aug 2023

: 28 Aug 2023 Diagnosed Diagnostician : Sean Felton

**EDL NA Recips-Grand Blanc** 

Grand Blanc Powerstation, 2361 West Grand Blanc Road Grand Blanc, MI US 48439

> Contact: Tony Saint Marie tony.saintmarie@edlenergy.com T:

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: