

## **PROBLEM SUMMARY**

# KAESER SK 19 2182448 (S/N 1694)

Compressor Fluid

#### KAESER SIGMA (OEM) S-460 (--- GAL)

#### COMPONENT CONDITION SUMMARY



#### RECOMMENDATION

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

# Sample Rating Trend ISO

PROBLEMATIC TEST RESULTS							
Sample Status			ABNORMAL	ABNORMAL	NORMAL		
Particles >6µm	ASTM D7647	>1300	<u> </u>		603		
Particles >14µm	ASTM D7647	>80	<b>A</b> 730		32		
Particles >21µm	ASTM D7647	>20	<u> </u>		9		
Particles >38µm	ASTM D7647	>4	<u> </u>		2		
Oil Cleanliness	ISO 4406 (c)	>/17/13	<u> </u>		16/12		

Customer Id: MCKNORMA Sample No.: KCPA004657 Lab Number: 05935422 Test Package: IND 2



To manage this report scan the QR code

*To discuss the diagnosis or test data:* Don Baldridge +1 <u>don.b505@comcast.net</u>

*To change component or sample information:* Customer Service +1 1-800-237-1369 <u>customerservice@wearcheck.com</u> There are no recommended actions for this sample.

#### **HISTORICAL DIAGNOSIS**



No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.All component wear rates are normal. Moderate concentration of visible dirt/debris present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



30 Oct 2020 Diag: Angela Borella



07 Jul 2021 Diag: Angela Borella

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.All component wear rates are normal. The amount and size of particulates present in the system are acceptable. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



view repor



The filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.All component wear rates are normal. Moderate concentration of visible dirt/debris present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.





#### Report Id: MCKNORMA [WUSCAR] 05935422 (Generated: 08/28/2023 19:24:48) Rev: 1



### **OIL ANALYSIS REPORT**

## KAESER SK 19 2182448 (S/N 1694)

**Compressor** Fluid

KAESER SIGMA (OEM) S-460 (--- GAL)

#### DIAGNOSIS

#### Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is a high amount of particulates present in the oil.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA004657	KCP35329	KCP33132
Sample Date		Client Info		24 Aug 2023	17 Feb 2022	07 Jul 2021
Machine Age	hrs	Client Info		35792	29073	27012
Oil Age	hrs	Client Info		0	3620	5459
Oil Changed		Client Info		N/A	Not Changd	Changed
Sample Status				ABNORMAL	ABNORMAL	NORMAL
		mothod	limit/bass	ourropt	biotonut	biotony2
		methou		Current	Thistory	inistory2
Iron	ppm	ASTM D5185m	>50	<1	3	<1
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	<1
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	<1
Aluminum	ppm	ASTM D5185m	>10	0	<1	0
Lead	ppm	ASTM D5185m	>10	0	<1	0
Copper	ppm	ASTM D5185m	>50	11	7	14
Tin	ppm	ASTM D5185m	>10	0	0	0
Antimony	ppm	ASTM D5185m			0	1
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	5
Barium	ppm	ASTM D5185m	90	0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m	90	27	59	12
Calcium	ppm	ASTM D5185m	2	0	4	0
Phosphorus	ppm	ASTM D5185m		0	2	2
Zinc	ppm	ASTM D5185m		16	21	4
Sulfur	ppm	ASTM D5185m		20803	16805	16005
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	1	0
Sodium	ppm	ASTM D5185m		17	33	6
Potassium	ppm	ASTM D5185m	>20	1	6	2
Water	%	ASTM D6304	>0.05	0.014	0.012	0.009
ppm Water	ppm	ASTM D6304	>500	148.9	123.8	91.7
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		13896		3467
Particles >6µm		ASTM D7647	>1300	<b>4</b> 5426		603
Particles >14um		ASTM D7647	>80	<b>A</b> 730		32
Particles >21um		ASTM D7647	>20	<u> </u>		9
Particles >38um		ASTM D7647	>4	<u>6</u>		2
Particles >71um		ASTM D7647	>3	0		0
Oil Cleanliness		ISO 4406 (c)	>/17/13	21/20/17		16/12
			l'actual de la companya de la		1	
FLUID DEGRADA	HON	method	limit/base	current	history1	history2

Acid Number (AN) mg KOH

mg KOH/g ASTM D8045 0.4

**0.31** 0.34 0.351

Report Id: MCKNORMA [WUSCAR] 05935422 (Generated: 08/28/2023 19:24:49) Rev: 1

Contact/Location: ERIC BERLO - MCKNORMA



## **OIL ANALYSIS REPORT**







VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	LIGHT	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	🔺 MODER	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	46	44.1	42.6	44.6
SAMPLE IMAGES	;	method	limit/base	current	history1	history2
Color						









Contact/Location: ERIC BERLO - MCKNORMA