



OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
601405 - FORD EXPLORER (S/N 1FM5K7D85EGB15938)

Component
Gasoline Engine

Fluid
PETRO CANADA DURON ADVANCED 5W30 (--- GAL)

DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	SBP0004641	---	---
Sample Date	Client Info	23 Aug 2023	---	---
Machine Age	hrs Client Info	105354	---	---
Oil Age	hrs Client Info	7500	---	---
Oil Changed	Client Info	Changed	---	---
Sample Status		NORMAL	---	---

CONTAMINATION

method	limit/base	current	history1	history2
Glycol	WC Method	NEG	---	---

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >150	7	---	---
Chromium	ppm ASTM D5185m >20	<1	---	---
Nickel	ppm ASTM D5185m >5	0	---	---
Titanium	ppm ASTM D5185m	0	---	---
Silver	ppm ASTM D5185m >2	0	---	---
Aluminum	ppm ASTM D5185m >40	2	---	---
Lead	ppm ASTM D5185m >50	0	---	---
Copper	ppm ASTM D5185m >155	7	---	---
Tin	ppm ASTM D5185m >10	0	---	---
Vanadium	ppm ASTM D5185m	0	---	---
Cadmium	ppm ASTM D5185m	0	---	---

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	44	---	---
Barium	ppm ASTM D5185m 0	6	---	---
Molybdenum	ppm ASTM D5185m 43	82	---	---
Manganese	ppm ASTM D5185m 0	1	---	---
Magnesium	ppm ASTM D5185m 920	596	---	---
Calcium	ppm ASTM D5185m 1330	1120	---	---
Phosphorus	ppm ASTM D5185m 790	755	---	---
Zinc	ppm ASTM D5185m 880	900	---	---
Sulfur	ppm ASTM D5185m 2200	3561	---	---

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >30	15	---	---
Sodium	ppm ASTM D5185m >400	5	---	---
Potassium	ppm ASTM D5185m >20	0	---	---
Fuel	% ASTM D3524 >4.0	<1.0	---	---

INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844	0	---	---
Nitration	Abs/cm *ASTM D7624 >20	7.8	---	---
Sulfation	Abs/.1mm *ASTM D7415 >30	20.6	---	---

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	13.6	---	---
Base Number (BN)	mg KOH/g ASTM D2896 12.0	4.2	---	---







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2	
White Metal	scalar	*Visual	NONE	NONE	---	---
Yellow Metal	scalar	*Visual	NONE	NONE	---	---
Precipitate	scalar	*Visual	NONE	NONE	---	---
Silt	scalar	*Visual	NONE	NONE	---	---
Debris	scalar	*Visual	NONE	NONE	---	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---	---
Appearance	scalar	*Visual	NORML	NORML	---	---
Odor	scalar	*Visual	NORML	NORML	---	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---	---
Free Water	scalar	*Visual		NEG	---	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	10.0	8.2	---	---

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : SBP0004641 **Received** : 28 Aug 2023
Lab Number : **05935937** **Diagnosed** : 01 Sep 2023
Unique Number : 10621208 **Diagnostician** : Doug Bogart
Test Package : FLEET (Additional Tests: FuelDilution, PercentFuel)

Constructors Inc. - 603659
 1815 Y Street
 Lincoln, NE
 US 68508
 Contact: Jack Linhart
 jackl@constructorslincoln.com
 T: (402)434-2157
 F:

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)