

## **OIL ANALYSIS REPORT**

CATERPILLAR DIESEL. 131718

Sample Rating Trend



Component
Left Auger Pump Drive
Fluid

## MOBIL MOBILUBE HD 85W140 (--- GAL)

CONSTRUCTORS, INC

DIAGNOSIS	SAMPLE INFORM	<b>IATION</b>	method	limit/base	current	history1	history2
Recommendation	Sample Number		Client Info		SBP0004629	SBP0004466	SBP0001380
Resample at the next service interval to monitor.	Sample Date		Client Info		22 Aug 2023	11 May 2023	04 Oct 2022
Wear	Machine Age	hrs	Client Info		6408	5840	5349
All component wear rates are normal.	Oil Age	hrs	Client Info		568	491	537
	Oil Changed		Client Info		N/A	Changed	Changed
<b>Contamination</b> There is no indication of any contamination in the	Sample Status				NORMAL	NORMAL	NORMAL
oil.	WEAR METALS		mathad	limit/base			
Fluid Condition			method	limit/base		history1	history2
The condition of the oil is acceptable for the time in	Iron	ppm	ASTM D5185m		46	92	162
service.	Chromium	ppm	ASTM D5185m		0	<1	1
	Nickel	ppm	ASTM D5185m	>10	0	<1	0
	Titanium	ppm	ASTM D5185m		<1	0	0
	Silver	ppm	ASTM D5185m		0	0	0
	Aluminum	ppm	ASTM D5185m		0	0	<1
	Lead	ppm	ASTM D5185m		0	0	<1
	Copper	ppm	ASTM D5185m		0	<1	<1
	Tin	ppm	ASTM D5185m		<1	0	0
	Vanadium	ppm	ASTM D5185m		<1	0	0
	Cadmium	ppm	ASTM D5185m		0	0	0
	ADDITIVES		method	limit/base	current	history1	history2
	Boron	ppm	ASTM D5185m		279	244	175
	Barium	ppm	ASTM D5185m		0	0	0
	Molybdenum	ppm	ASTM D5185m		5	6	2
	Manganese	ppm	ASTM D5185m		<1	1	2
	Magnesium	ppm	ASTM D5185m		2	<1	<1
	Calcium	ppm	ASTM D5185m		9	15	139
	Phosphorus	ppm	ASTM D5185m		1020	1014	1497
	Zinc		ASTM D5185m		14	27	122
	Sulfur	ppm ppm	ASTM D5185m		24138	20547	28219
	CONTAMINANTS		method	limit/base		history1	history2
	Silicon		ASTM D5185m	mmbase			
	Sodium	ppm	ASTM D5185m		6	4	<1
	Potassium	ppm	ASTM D5185m	>20	<1 0	0 <1	0 <1
		ppm					
	VISUAL		method	limit/base		history1	history2
	White Metal	scalar	*Visual	NONE	NONE	NONE	MODER
	Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
	Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
	Silt	scalar	*Visual	NONE	NONE	NONE	NONE
	Debris	scalar	*Visual	NONE	NONE	NONE	NONE
	Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
	Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
	Odor	scalar	*Visual	NORML	NORML	NORML	NORML
	Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
	Free Water	scalar	*Visual		NEG	NEG	NEG
	FLUID PROPERT	IES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445		344	320	200
							Description in the second



## **OIL ANALYSIS REPORT**



