


OIL ANALYSIS REPORT

Sample Rating Trend



DIRT



METRO **METRO 20013**

Component

Front Differential

NOT GIVEN (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor. Please note that this is a corrected copy for laboratory elemental data.

Wear

Gear wear is indicated.

Contamination

There is a high amount of silt (particulates < 14 microns in size) present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Feb 2019	Dec2019 Jun2020	Mar2021 Nov2021 Aug2022	Aug2023	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0843195	WC0728401	WC0661183
Sample Date		Client Info		21 Aug 2023	08 Aug 2022	08 Nov 2021
Machine Age	mls	Client Info		417114	236186	276933
Oil Age	mls	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>500	<u></u> 601	▲ 538	498
Chromium	ppm	ASTM D5185m	>10	4	5	4
Nickel	ppm	ASTM D5185m	>10	2	3	<1
Titanium	ppm	ASTM D5185m		0	<1	<1
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	8	4	4
Lead	ppm	ASTM D5185m	>25	0	<1	0
Copper	ppm	ASTM D5185m	>100	3	3	3
Tin	ppm	ASTM D5185m	>10	0	<1	0
Antimony	ppm	ASTM D5185m	>5			0
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		445	418	349
Barium	ppm	ASTM D5185m		31	0	5
Molybdenum	ppm	ASTM D5185m		0	1	1
Manganese	ppm	ASTM D5185m		7	19	18
Magnesium	ppm	ASTM D5185m		13	0	2
Calcium	ppm	ASTM D5185m		8	13	15
Phosphorus	ppm	ASTM D5185m		2047	2000	1967
Zinc	ppm	ASTM D5185m		39	12	15
Sulfur	ppm	ASTM D5185m		25056	23614	21297
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>75	<u> </u>	<u> </u>	<u> </u>
Sodium	ppm	ASTM D5185m		12	11	10
Potassium	ppm	ASTM D5185m	>20	7	4	2
Water	%	ASTM D6304	>.2	0.033	0.001	0.054
ppm Water	ppm	ASTM D6304	>2000	338.7	10.3	546.7
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>20000	162316	△ 97920	
Particles >6µm		ASTM D7647	>5000	<u>▲</u> 37323	<u>▲</u> 5248	
Particles >14μm		ASTM D7647	>640	54	33	
Particles >21µm		ASTM D7647	>160	10	6	
Particles >38μm		ASTM D7647	>40	1	0	
Particles >71µm		ASTM D7647	>10	0	0	
Oil Cleanliness		ISO 4406 (c)	>21/19/16	<u>25/22/13</u>	<u>4</u> 24/20/12	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2



OIL ANALYSIS REPORT

