

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



WILTER 102-B (S/N 5757)

Component

Screw Compressor

TULCO LUBSOIL 2150 SYNTHETIC 150 (10

Recommendation

Resample at the next service interval to monitor. Please note that this is a corrected copy for oil type and diagnostic comment updates concerning water content.

Wear

All component wear rates are normal.

Contamination

The water content is negligible. No other contaminants were detected in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

05 GAL)				Aug 2023		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		TO60001273		
Sample Date		Client Info		10 Aug 2023		
Machine Age	hrs	Client Info		85586		
Oil Age	hrs	Client Info		85586		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>60	<1		
Chromium	ppm	ASTM D5185m	>4	<1		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>5	<1		
Lead	ppm	ASTM D5185m	>10	<1		
Copper	ppm	ASTM D5185m	>30	<1		
Tin	ppm	ASTM D5185m	>15	<1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		7		
Calcium	ppm	ASTM D5185m		3		
Phosphorus	ppm	ASTM D5185m		126		
Zinc	ppm	ASTM D5185m		23		
Sulfur	ppm	ASTM D5185m		105		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	<1		
Sodium	ppm	ASTM D5185m		1		
Potassium	ppm	ASTM D5185m	>20	4		
Water	%	ASTM D6304	>2.0	0.388		
ppm Water	ppm	ASTM D6304	>20000	3880.0		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	514		
Particles >6µm		ASTM D7647	>2500	151		
Particles >14μm		ASTM D7647	>320	22		
Particles >21µm		ASTM D7647	>80	5		
Particles >38µm		ASTM D7647	>20	0		
Particles >71µm		ASTM D7647	>4	0		
Oil Cleanliness		ISO 4406 (c)	>20/18/15	16/14/12		
FLUID DEGRADA	NOITA	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.90		



OIL ANALYSIS REPORT

