

### **OIL ANALYSIS REPORT**

Sample Rating Trend

NORMAL

# VILTER 105-E (S/N 5324)

Screw Compressor Fluid TULCO LUBSOIL 2150 SYNTHETIC 150 (105 GAL)

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor. Please note that this is a corrected copy for oil type and diagnostic comment updates concerning water content.

#### Wear

All component wear rates are normal.

#### Contamination

The water content is negligible. No other contaminants were detected in the oil. The amount and size of particulates present in the system are acceptable.


#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

				Aug2023		
SAMPLE INFORM	<b>MATION</b>	method	limit/base	current	history1	history2
Sample Number		Client Info		TO60001281		
Sample Date		Client Info		10 Aug 2023		
Machine Age	hrs	Client Info		64384		
Oil Age	hrs	Client Info		64384		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>60	0		
Chromium	ppm	ASTM D5185m	>4	<1		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>5	0		
Lead	ppm	ASTM D5185m	>10	<1		
Copper	ppm	ASTM D5185m	>30	<1		
Tin	ppm	ASTM D5185m	>15	<1		
Vanadium	ppm	ASTM D5185m		<1		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		7		
Calcium	ppm	ASTM D5185m		0		
Phosphorus	ppm	ASTM D5185m		64		
Zinc	ppm	ASTM D5185m		17		
Sulfur	ppm	ASTM D5185m		116		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	<1		
Sodium	ppm	ASTM D5185m		<1		
Potassium	ppm	ASTM D5185m	>20	4		
Water	%	ASTM D6304	>2.0	0.321		
ppm Water	ppm	ASTM D6304	>20000	3219.7		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	754		
Particles >6µm		ASTM D7647	>2500	173		
Particles >14µm		ASTM D7647	>320	15		
Particles >21µm		ASTM D7647	>80	6		
Particles >38µm		ASTM D7647	>20	1		
Particles >71µm		ASTM D7647	>4	0		
Oil Cleanliness		ISO 4406 (c)	>20/18/15	17/15/11		
FLUID DEGRADA		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.63		



## **OIL ANALYSIS REPORT**



Contact/Location: TROY WATSON - COAFARNM

T:

F:

20 23

8

1400

1999 Cle