

PROBLEM SUMMARY



TURBO FAN (S/N 31010101)

Bearing Fluid SHELL TELLUS 46 (46 GAL)

COMPONENT CONDITION SUMMARY



RECOMMENDATION

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

PROBLEMATIC TES	ST RESULTS				
Sample Status			ATTENTION	NORMAL	
Particles >6µm	ASTM D7647	>1300	<u> </u>		
Oil Cleanliness	ISO 4406 (c)	>/17/14	20/18/14		

Customer Id: LEPWAV Sample No.: WC0776130 Lab Number: 05937653 Test Package: IND 2



To manage this report scan the QR code

To discuss the diagnosis or test data: Doug Bogart +1 (800)237-1369 x4016 <u>dougb@wearcheckusa.com</u>

To change component or sample information: Customer Service +1 1-800-237-1369 customerservice@wearcheck.com There are no recommended actions for this sample.

HISTORICAL DIAGNOSIS

01 Apr 2005 Diag:



Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the component. The condition of oil is suitable for further service.





OIL ANALYSIS REPORT

Sample Rating Trend

ISO

TURBO FAN (S/N 31010101)

Bearing Fluid

SHELL TELLUS 46 (46 GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a moderate amount of silt (particulates < 14 microns in size) present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0776130	WCI2058278	
Sample Date		Client Info		15 Aug 2023	01 Apr 2005	
Machine Age	yrs	Client Info		20	21345	
Oil Age	yrs	Client Info		1	4383	
Oil Changed		Client Info		Not Changd	Not Changd	
Sample Status				ATTENTION	NORMAL	
WEAR METALS		method	limit/base	current	historv1	historv2
Iron	nom	ASTM D5185m	> 20	.1	2	
Chromium	ppm	ASTM D5185m	>20	0	0	
Nickel	ppm	ASTM D5185m	>20	-1	0	
Titanium	nnm	ASTM D5185m	20	0	0	
Silver	nom	ASTM D5185m		0	0	
Aluminum	nnm	ASTM D5185m	>20	0	0	
Lead	nom	ASTM D5185m	>20	0	2	
Conner	nnm	ASTM D5185m	>20	0	~1	
Tin	ppm	ASTM D5185m	>20	0	0	
Antimony	ppm	ASTM D5185m	200		9	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	nnm	ASTM D5185m		0	0	
Cadimidin	ppm	AUTIVI DUTUUIII		Ũ	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0.0	0	0	
Barium	ppm	ASTM D5185m	0	2	0	
Molybdenum	ppm	ASTM D5185m	0	0	<1	
Manganese	ppm	ASTM D5185m		0	0	
Magnesium	ppm	ASTM D5185m	11	60	<1	
Calcium	ppm	ASTM D5185m	35	19	79	
Phosphorus	ppm	ASTM D5185m	266	283	342	
Zinc	ppm	ASTM D5185m	276	338	404	
Sulfur	ppm	ASTM D5185m	1847	724	1154	
CONTAMINANTS	6	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	2	<1	
Sodium	ppm	ASTM D5185m		0	0	
Potassium	ppm	ASTM D5185m	>20	0	0	
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		8387		
Particles >6µm		ASTM D7647	>1300	<u> </u>		
Particles >14µm		ASTM D7647	>160	90		
Particles >21µm		ASTM D7647	>40	28		
Particles >38µm		ASTM D7647	>10	1		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>/17/14	20/18/14		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/a	ASTM D8045	0.36	0.42	0.519	
(-)	0 - 0				-	



OIL ANALYSIS REPORT







VISUAL		method	limit/base	current	history1	history2
Vhite Metal	scalar	*Visual	NONE	NONE	NONE	
ellow Metal	scalar	*Visual	NONE	NONE	NONE	
recipitate	scalar	*Visual	NONE	NONE	NONE	
iilt	scalar	*Visual	NONE	NONE	NONE	
ebris	scalar	*Visual	NONE	NONE	NONE	
and/Dirt	scalar	*Visual	NONE	NONE	NONE	
ppearance	scalar	*Visual	NORMI	NORMI	NORMI	
)dor	scalar	*Visual	NORMI	NORMI	NORMI	
mulsified Water	scalar	*Visual	~2	NEG	NEG	
ree Water	scalar	*Vieual	~_	NEG	NEG	
		Visual	Prod 10 /le on one			
				current		nistory2
ISC @ 40°C	cSt	ASTM D445	46.99	47.15	45.11	
isc @ 100°C	cSt	ASTM D445	6.76	7.34		
iscosity Index (VI)	Scale	ASTM D2270	96	117		
SAMPLE IMAGES	;	method	limit/base	current	history1	history2
color					no image	no image
ottom					no image	no image
GRAPHS						
Ferrous Alloys			401.5	AParticle Coun	t	2
iron			491,52	I		T ²
sessesses chromium			122,88	0 -		-2
			30,72	0		
			7.00			
/02			(III) (23			***************************************
Aprl			1,92 (ber 1	0-		-1
Non-ferrous Metals			ticles 4			1
	•		of par		S	
copper			and the second s	0-		-1
icau tin			in in	0 -		-1
				° Bereve mal	1	1
11/05			5/23	2-		
Apr			Aug1	0		
Viscosity @ 40°C			-	⁴ μ 6μ Acid Number	14μ 21μ	38µ 71µ
, e			₽0.6			
Abnormal			HO 0.4	8		
Base			Ĕ 0.3	6 Base		
				4		
Abnormal			20.1	2		
- 20/				/02		
Aprl			Aug 15	Apr1		
VearCheck USA - 5 VC0776130 F 05937653 C 0622924 C	01 Madia Received Diagnos Diagnosi	son Ave., Ca d : 29 / ed : 04 \$ tician : Dou	ry, NC 2751 Aug 2023 Sep 2023 Ig Bogart	з і	EPRINO FOOL 400	DS - WAVER LEPRINO A WAVERLY, I

Report Id: LEPWAV [WUSCAR] 05937653 (Generated: 09/05/2023 18:48:31) Rev: 1

To discuss this sample report,

Certificate L2367

Sample No. Lab Number Unique Number Test Package

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: ED TWINING - LEPWAV

F: (570)882-7290

Т: