PROBLEM SUMMARY

Sample Rating Trend



SULLUBE SULLAIR 38121010529 - MACO Component

Compressor

COMPONENT CONDITION SUMMARY



RECOMMENDATION

We advise that you follow the water drain-off procedure for this component. We recommend an early resample to monitor this condition.

| PROBLEMATIC TEST RESULTS | | | | | | | |
|--------------------------|--------|------------|-------|---------------|--|--|--|
| Sample Status | | | | SEVERE | | | |
| Water | % | ASTM D6304 | >0.1 | e 1.12 | | | |
| ppm Water | ppm | ASTM D6304 | >1000 | 🛑 11200 | | | |
| Emulsified Water | scalar | *Visual | >0.1 | 0.2% | | | |

Customer Id: UCBLAMEM Sample No.: UCS05938354 Lab Number: 05938354 Test Package: IND 2



To manage this report scan the QR code

To discuss the diagnosis or test data: Angela Borella +1 800-237-1369 angela.borella@wearcheckusa.com

To change component or sample information: Customer Service +1 1-800-237-1369 customerservice@wearcheck.com

| RECOMMENDED ACTIONS | | | | | | |
|---------------------|--------|------|---------|---|--|--|
| Action | Status | Date | Done By | Description | | |
| Water Drain-off | | | ? | We advise that you follow the water drain-off procedure for this component. | | |
| Resample | | | ? | We recommend an early resample to monitor this condition. | | |

HISTORICAL DIAGNOSIS

<u>Sullivan</u> Palatek.

OIL ANALYSIS REPORT

Sample Rating Trend

WATER

Area SULLUBE Machine Id SULLAIR 38121010529 - MACO Component

Compressor

DIAGNOSIS

Recommendation

We advise that you follow the water drain-off procedure for this component. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

Contamination

There is a high concentration of water present in the oil.

Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.


| SAMPLE INFORM | IATION | method | limit/base | current | history1 | history2 |
|---|--|--|---|--|--------------------------------------|------------------------------|
| Sample Number | | Client Info | | UCS05938354 | | |
| Sample Date | | Client Info | | 19 Jul 2023 | | |
| Machine Age | hrs | Client Info | | 3289 | | |
| Oil Age | hrs | Client Info | | 0 | | |
| Oil Changed | | Client Info | | N/A | | |
| Sample Status | | | | SEVERE | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >50 | <1 | | |
| Chromium | ppm | ASTM D5185m | >10 | 0 | | |
| Nickel | ppm | ASTM D5185m | | <1 | | |
| Titanium | ppm | ASTM D5185m | | 0 | | |
| Silver | ppm | ASTM D5185m | | 0 | | |
| Aluminum | ppm | ASTM D5185m | >25 | <1 | | |
| Lead | ppm | ASTM D5185m | >25 | 0 | | |
| Copper | ppm | ASTM D5185m | >50 | <1 | | |
| Tin | ppm | ASTM D5185m | >15 | <1 | | |
| Vanadium | ppm | ASTM D5185m | | <1 | | |
| Cadmium | ppm | ASTM D5185m | | <1 | | |
| | | | | | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| ADDITIVES Boron | ppm | method ASTM D5185m | limit/base | current | history1 | history2 |
| | ppm ppm | | | | | |
| Boron | | ASTM D5185m | 1 | 1 | | |
| Boron Barium | ppm | ASTM D5185m ASTM D5185m | 1 730 0 | 1 350 | | |
| Boron Barium Molybdenum | ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m | 1 730 0 | 1 350 0 | | |
| Boron Barium Molybdenum Manganese | ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m | 1 730 0 0.0 0 | 1 350 0 0 | | |
| Boron Barium Molybdenum Manganese Magnesium | ppm ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m | 1 730 0 0.0 0 | 1 350 0 0 <1 | | |
| Boron Barium Molybdenum Manganese Magnesium Calcium | ppm ppm ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m | 1 730 0 0.0 0 0 | 1 350 0 <1 2 | | |
| Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus | ppm ppm ppm ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m | 1 730 0 0.0 0 0 0 | 1 350 0 <1 2 4 | | |
| Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc | ppm ppm ppm ppm ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m | 1 730 0 0.0 0 0 0 0 | 1 350 0 <1 2 4 16 | | |
| Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur | ppm ppm ppm ppm ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m | 1 730 0 0.0 0 0 0 0 590 | 1 350 0 <1 2 4 16 301 | | |
| Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS | ppm ppm ppm ppm ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m | 1 730 0 0.0 0 0 0 0 590 limit/base | 1 350 0 <1 2 4 16 301 current | history1 | history2 |
| Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon | ppm ppm ppm ppm ppm ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m | 1 730 0 0.0 0 0 0 0 590 limit/base | 1 350 0 <1 2 4 16 301 <i>current</i> 1 | history1 | history2 |
| Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium | ppm ppm ppm ppm ppm ppm ppm ppm | ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m | 1 730 0 0.0 0 0 0 0 590 limit/base >25 | 1 350 0 <1 2 4 16 301 <i>current</i> 1 2 | history1 | history2 |
| Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium | ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm | ASTM D5185m ASTM D5185m | 1 730 0 0.0 0 0 0 0 0 590 limit/base >25 | 1 350 0 <1 2 4 16 301 <i>current</i> 1 2 1 2 1 4 | history1 | history2 |
| Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium Water | ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm | ASTM D5185m ASTM D5185m | 1 730 0 0.0 0 0 0 0 590 limit/base >25 >20 >20 | 1 350 0 0 <1 2 4 16 301 | history1 | history2 |



OIL ANALYSIS REPORT







| | VISUAL | | method | limit/base | e current | history1 | history2 | | |
|---|---|--------|-----------|------------------------|-------------|--|-----------|--|--|
| | White Metal | scalar | *Visual | NONE | NONE | | | | |
| | Yellow Metal | scalar | *Visual | NONE | NONE | | | | |
| | Precipitate | scalar | *Visual | NONE | NONE | | | | |
| | Silt | scalar | *Visual | NONE | NONE | | | | |
| | Debris | scalar | *Visual | NONE | NONE | | | | |
| | Sand/Dirt | scalar | *Visual | NONE | NONE | | | | |
| | Appearance | scalar | *Visual | NORML | NORML | | | | |
| 3 | Odor | scalar | *Visual | NORML | NORML | | | | |
| | Emulsified Water | scalar | *Visual | >0.1 | • 0.2% | | | | |
| | Free Water | scalar | *Visual | | NEG | | | | |
| | FLUID PROPER | TIES | method | limit/base | current | history1 | history2 | | |
| | Visc @ 40°C | cSt | ASTM D445 | 42.8 | 39.5 | | | | |
| | SAMPLE IMAGE | S | method | limit/base | current | history1 | history2 | | |
| | Color | | | | | no image | no image | | |
| | Bottom | | | | | no image | no image | | |
| | Ferrous Alloys | | | Juli9/23 | | | | | |
| | nonnentous meta | 115 | | Jul 19/23 | | | | | |
| | Viscosity @ 40°C | | | | Acid Number | | | | |
| | Abnormal | | | (B/H | 15 - Base | | | | |
| | 0 45 Base | | | Acid Number (mg KOH/g) | 10 | | | | |
| | () 45 Base 8 *********************************** | | | nber (i | 05 | | | | |
| | Abnormal | | | | | | | | |
| | 35 | | | | .00 | | | | |
| | Juli 9/23 | | | Jul19/23 | Jul19/23 | | CC 0 11.1 | | |
| | - | | | - | | | - | | |
| Laboratory Sample No. Lab Number Unique Number Test Package | : WearCheck USA - 501 Madison Ave., Cary, NC 27513 : UCS05938354 Received : 30 Aug 2023 : 05938354 Diagnosed : 31 Aug 2023 : 10628966 Diagnostician : Angela Borella : IND 2 (Additional Tests: KF) contact Customer Service at 1-800-237-1369. | | | | | BLAKE AND PENDLETOI MEMPHIS, TI US 3813 Contact: JAY GIANNIN JGIANNINI@BLAKEANDPENDLETON.COI | | | |

ŝ

ST.

ø

oks: