


# **OIL ANALYSIS REPORT**



**NORMAL** 



Machine Id

## heater

Component

**Heat Transfer Fluid** 

**EASTMAN THERMINOL 55 (--- GAL)** 

### Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the fluid. The amount and size of particulates present in the system are acceptable.

### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the fluid is suitable for further service.

						Y
			Sep2023			
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		TO10002571		
Sample Date		Client Info		15 Sep 2023		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed	1113	Client Info		N/A		
Sample Status		Ciletit iiilo		NORMAL		
		اه م ملخ م ما	live it /le e e e			
WEAR METALS		method	limit/base	current	history1	history2
lron	ppm	ASTM D5185m	>200	1		
Chromium	ppm	ASTM D5185m	>21	0		
Nickel	ppm	ASTM D5185m	>21	<1		
Titanium	ppm	ASTM D5185m	>21	0		
Silver	ppm	ASTM D5185m	>21	0		
Aluminum	ppm	ASTM D5185m	>21	0		
Lead	ppm	ASTM D5185m	>21	0		
Copper	ppm	ASTM D5185m	>21	0		
Tin	ppm	ASTM D5185m	>21	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		0		
Calcium	ppm	ASTM D5185m		0		
Phosphorus	ppm	ASTM D5185m		0		
Zinc	ppm	ASTM D5185m		0		
Sulfur	ppm	ASTM D5185m		4		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon		ASTM D5185m	>25	0	Thistory	Historyz
	ppm					
Sodium	ppm	ASTM D5185m	>21	0		
Potassium	ppm	ASTM D5185m	>20	1		
Water opm Water	% ppm	ASTM D6304 ASTM D6304	>0.0601 >601	0.005 53.7		
	ppm					h:atam.0
FLUID CLEANLIN	NESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	. 10040000	100424		
Particles >6µm		ASTM D7647		24527		
Particles >14µm		ASTM D7647	>10240000	776		
Particles >21µm		ASTM D7647	>2560000	149		
Particles >38µm		ASTM D7647	>640000	4		
Particles >71μm		ASTM D7647	>160000	0		
Oil Cleanliness		ISO 4406 (c)	>/30/30	24/22/17		
FLUID DEGRADA	NOITA	method	limit/base	current	history1	history2
Acid Number (AN)	ma KOLVa	VCTM DOUVE		0.072		

Acid Number (AN)

mg KOH/g ASTM D8045

0.073



## **OIL ANALYSIS REPORT**

