



PROBLEM SUMMARY



Machine Id 6812659 (S/N 1005) Component

Compressor Fluid KAESER SIGMA (OEM) M-460 (--- GAL)

COMPONENT CONDITION SUMMARY



RECOMMENDATION

The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

PROBLEMATIC TEST RESULTS								
Sample Status			ATTENTION	NORMAL				
Particles >14µm	ASTM D7647	>80	<u> </u>	19				
Particles >21µm	ASTM D7647	>20	4 5	4				
Oil Cleanliness	ISO 4406 (c)	>/17/13	<u> </u>	15/11				

Customer Id: THMMOR Sample No.: KCPA006604 Lab Number: 05960633 Test Package: IND 2



To manage this report scan the QR code

To discuss the diagnosis or test data: Angela Borella +1 800-237-1369 angela.borella@wearcheckusa.com

To change component or sample information: Customer Service +1 1-800-237-1369 customerservice@wearcheck.com There are no recommended actions for this sample.

HISTORICAL DIAGNOSIS

15 Feb 2022 Diag: Jonathan Hester



15 Teb 2022 Diag. Conathan riest



Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.





OIL ANALYSIS REPORT

Sample Rating Trend

limit/base

current

SAMPLE INFORMATION method

ISO

history1

history2

Machine Id		
6812659	(S/N	1005)
Component	•	/

Compressor Fluid

KAESER SIGMA (OEM) M-460 (--- GAL)

DIAGNOSIS

Recommendation

The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a moderate amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.

Sampla Number		Client Info		KCPA006604	KCP40976	
Sample Number		Client Info				
Sample Date	la un			19 Sep 2023	15 Feb 2022	
Machine Age	hrs	Client Info		20738	15044	
Oil Age	hrs	Client Info		0	2200	
Oil Changed		Client Info		N/A	Changed	
Sample Status				ATTENTION	NORMAL	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1	<1	
Chromium	ppm	ASTM D5185m	>10	0	0	
Nickel	ppm	ASTM D5185m	>3	0	0	
Titanium	ppm	ASTM D5185m	>3	0	0	
Silver	ppm	ASTM D5185m	>2	0	0	
Aluminum	ppm	ASTM D5185m	>10	1	<1	
Lead	ppm	ASTM D5185m	>10	0	0	
Copper	ppm	ASTM D5185m	>50	6	12	
Tin	ppm	ASTM D5185m	>10	<1	0	
Antimony	ppm	ASTM D5185m			0	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	
Barium	ppm	ASTM D5185m	90	0	0	
Molybdenum	ppm	ASTM D5185m	0	<1	0	
Manganese	ppm	ASTM D5185m		<1	0	
Magnesium	ppm	ASTM D5185m	100	15	0	
Calcium	ppm	ASTM D5185m	0	<1	0	
Phosphorus	ppm	ASTM D5185m	0	4	0	
Zinc	ppm	ASTM D5185m	0	9	0	
Sulfur	ppm	ASTM D5185m	23500	23109	13515	
CONTAMINANTS	S	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	<1	
Sodium	ppm	ASTM D5185m		6	0	
Potassium	ppm	ASTM D5185m	>20	2	0	
Water	%	ASTM D6304	>0.05	0.012	0.003	
ppm Water	ppm	ASTM D6304	>500	122.1	37.3	
FLUID CLEANLIN	VESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		3026	1082	
Particles >6µm		ASTM D7647	>1300	1071	233	
Particles >14µm		ASTM D7647	>80	<u> </u>	19	
Particles >21µm		ASTM D7647	>20	<u> </u>	4	
Particles >38µm		ASTM D7647	>4	3	0	
Particles >71µm		ASTM D7647	>3	1	0	
Oil Cleanliness		ISO 4406 (c)	>/17/13	19/17/14	15/11	
FLUID DEGRAD	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	1.0	0.41	0.19	
(16:38) Bev: 1						


Report Id: THMMOR [WUSCAR] 05960633 (Generated: 09/27/2023 15:16:38) Rev: 1


Contact/Location: Service Manager - THMMOR




Built for a lifetime

OIL ANALYSIS REPORT








44


Se

Base

Sev

Feb 1





Certificate L2367