


OIL ANALYSIS REPORT

NIAGARA WATER BRIGHAM CITY UT H1 HUSKY

Component

Hydraulic System

NOT GIVEN (--- GAL)





Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		0ct2022	Feb 2023 Mar 2023	May2023 Aug2023	Sep 2023	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PTK0004335	PTK0004343	PTK0004338
Sample Date		Client Info		19 Sep 2023	21 Aug 2023	24 May 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	31	28	24
Chromium	ppm	ASTM D5185m	>10	<1	<1	<1
Nickel	ppm	ASTM D5185m	>10	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>10	0	<1	<1
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m		2	1	1
Tin	ppm		>10	<1	0	0
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		0	0	0
Calcium	ppm	ASTM D5185m		114	115	115
Phosphorus	ppm	ASTM D5185m		435	453	453
Zinc	ppm	ASTM D5185m		4	6	1
Sulfur	ppm	ASTM D5185m		1592	1679	1809
CONTAMINANTS	5	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	2	2	1
Sodium	ppm	ASTM D5185m		0	1	<1
Potassium	ppm	ASTM D5185m	>20	0	0	0
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	2327	1003	1424
Particles >6µm		ASTM D7647	>1300	800	274	372
Particles >14µm		ASTM D7647	>160	91	28	22
Particles >21µm		ASTM D7647		24	7	7
Particles >38µm		ASTM D7647	>10	1	0	0
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>19/17/14	18/17/14	17/15/12	18/16/12
FLUID DEGRADA	NOITA	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.20	0.22	0.18



OIL ANALYSIS REPORT







Certificate L2367

Laboratory

Sample No. Lab Number : 05961214 **Unique Number** : 10662427 Test Package : MOB 2

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 26 Sep 2023 : PTK0004335

: 27 Sep 2023 Diagnosed : Don Baldridge Diagnostician

NIAGARA BOTTLING - BRIGHAM CITY 77 N INDUSTRIAL WAY

BRIGHAM CITY, UT US 84302

Contact: REX COLLEDGE

rcolledge@niagarawater.com T:

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

To discuss this sample report, contact Customer Service at 1-800-237-1369.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: