


OIL ANALYSIS REPORT

Area [1815397] SW06 (S/N 1678 606) Component

Gearbox

SHELL OMALA 220 (2 GAL)





Recommendation

Resample at the next service interval to monitor. (Customer Sample Comment: Monthly oil change and sample)

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

#2005 Sep2005 Sep2006 Feb2007 Oct2007 Sep2010 Apr20123 Aug2023									
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2			
Sample Number		Client Info		WC0807618	WC0807614	WC0834254			
Sample Date		Client Info		13 Sep 2023	18 Aug 2023	20 Jul 2023			
Machine Age	hrs	Client Info		4369	3787	3173			
Oil Age	hrs	Client Info		582	2074	530			
Oil Changed		Client Info		Changed	N/A	Changed			
Sample Status				NORMAL	NORMAL	NORMAL			
WEAR METALS		method	limit/base	current	history1	history2			
Iron	ppm	ASTM D5185m	>200	54	58	53			
Chromium	ppm	ASTM D5185m	>15	<1	0	<1			
Nickel	ppm	ASTM D5185m	>15	0	0	0			
Titanium	ppm	ASTM D5185m		0	0	0			
Silver	ppm	ASTM D5185m		0	0	0			
Aluminum	ppm	ASTM D5185m	>25	0	<1	<1			
Lead	ppm	ASTM D5185m	>100	0	0	0			
Copper	ppm	ASTM D5185m	>200	2	1	<1			
Tin	ppm	ASTM D5185m	>25	<1	<1	<1			
Vanadium	ppm	ASTM D5185m		0	0	0			
Cadmium	ppm	ASTM D5185m		0	0	0			
ADDITIVES		method	limit/base	current	history1	history2			
Boron	ppm	ASTM D5185m	4.4	0	0	0			
Barium	ppm	ASTM D5185m	0.0	0	0	<1			
Molybdenum	ppm	ASTM D5185m	0	0	0	0			
Manganese	ppm	ASTM D5185m		<1	<1	<1			
Magnesium	ppm	ASTM D5185m	0	<1	<1	4			
Calcium	ppm	ASTM D5185m	0	7	3	2			
Phosphorus	ppm	ASTM D5185m	215	208	214	211			
Zinc	ppm	ASTM D5185m	0	11	2	7			
Sulfur	ppm	ASTM D5185m	7039	10690	11101	13850			
CONTAMINANTS		method	limit/base	current	history1	history2			
Silicon	ppm	ASTM D5185m	>50	<1	0	4			
Sodium	ppm	ASTM D5185m		0	<1	1			
Potassium	ppm	ASTM D5185m	>20	0	0	0			
FLUID DEGRADA	TION	method	limit/base	current	history1	history2			
Acid Number (AN)	mg KOH/g	ASTM D8045		0.58	0.58	0.49			
VISUAL		method	limit/base	current	history1	history2			
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE			
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE			
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE			
Silt	scalar	*Visual	NONE	NONE	NONE	NONE			
Debris	scalar	*Visual	NONE	NONE	NONE	NONE			
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE			
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML			
Odor	scalar	*Visual	NORML	NORML	NORML	NORML			
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG			
Free Water	scalar	*Visual		NEG	NEG	NEG			
7 00 00\ D				,					




OIL ANALYSIS REPORT








FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	220	209	220	213
SAMPLE IMAGES		method	limit/base	current	history1	history2
Color						
Bottom						

GRAPHS













Certificate L2367

Laboratory Sample No. Lab Number **Unique Number** Test Package : IND 2

: WC0807618 : 05961353 : 10662566

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 26 Sep 2023 Diagnosed : 27 Sep 2023 Diagnostician : Don Baldridge

LEPRINO FOODS-FORT MORGAN

2400 EAST BEAVER AVE FORT MORGAN, CO US 80701

Contact: KEITH SCHULTE kschulte@leprinofoods.com

T: (970)542-4247 F: (970)542-4241

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: LEPFOR [WUSCAR] 05961353 (Generated: 09/27/2023 17:29:23) Rev: 1