

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id **PIERCE 752** Component Hydraulic System Fluid NOT GIVEN (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0843865	WCM1382152	WCM1357309
Sample Date		Client Info		12 Sep 2023	12 Sep 2017	27 Oct 2016
Machine Age	hrs	Client Info		0	1701	1578
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	nnm	ASTM D5185m	>20	1	<1	<1
Chromium	ppm			0	<1	<1
	ppm	ASTM D5185m		-		
Nickel	ppm		>10	<1	<1	<1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	10	0	0	0
Aluminum	ppm	ASTM D5185m		0	<1	<1
Lead	ppm	ASTM D5185m	>10	0	0	<1
Copper	ppm	ASTM D5185m		2	1	1
Tin	ppm	ASTM D5185m	>10	0	0	0
Antimony	ppm	ASTM D5185m			2	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	<1	<1
Barium	ppm	ASTM D5185m		0	<1	0
Molybdenum	ppm	ASTM D5185m		<1	<1	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m		2	3	2
Calcium	ppm	ASTM D5185m		124	157	158
Phosphorus	ppm	ASTM D5185m		460	694	654
Zinc	ppm	ASTM D5185m		587	871	863
Sulfur	ppm	ASTM D5185m		3965	2691	2788
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	<1	3	3
Sodium	ppm	ASTM D5185m		<1	<1	<1
Potassium	ppm	ASTM D5185m	>20	<1	2	4
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	LIGHT	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG



OIL ANALYSIS REPORT



	FLUID PROPER	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt /	ASTM D445		42.0	46.96	46.97
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
17	Color				no image	no image	no image
Sep12/17 Sep12/23	Bottom				no image	no image	no image
	GRAPHS						
	Ferrous Alloys	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		Sapi 12/23			
	Viscosity @ 40°C			Sep12/23 Sep12/23 N			
Laboratory Sample No. Lab Number Unique Number Test Package discuss this sample report, Denotes test methods that a atements of conformity to spec	: WearCheck USA - : WC0843865 : 05962565 : 10669116 : FLEET contact Customer Serv are outside of the ISO 1	501 Madiso Received Diagnosec Diagnostic vice at 1-800 17025 scope	on Ave., Cary : 27 Si d : 28 Si ian : Wes 0-237-1369. e of accredit	y, NC 27513 ep 2023 ep 2023 Davis ation.		1 Contact: CHIE hrfdjberger T:	ROSCOE FIRI 0544 MAIN S ROSCOE, I US 6107 F BERGEROI on@gmail.cor (815)623-786 F

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)