

# **PROBLEM SUMMARY**

# WHS Machine Id FRICK NH3 - WH5-BOOSTER 2 OK21020 (S/N S003DFEF1HAD3) Component

**Refrigeration Compressor** 

# JAX CRYOGUARD PLUS 68 (--- GAL)

# COMPONENT CONDITION SUMMARY



# RECOMMENDATION

Resample at the next service interval to monitor.

PROBLEMATIC TEST RESULTS								
Sample Status			ATTENTION	NORMAL	ATTENTION			
Particles >4µm	ASTM D7647	>10000	<u> </u>	588	<b>1</b> 1876			
Particles >6µm	ASTM D7647	>2500	<b>A</b> 3218	152	<b>a</b> 2504			
Oil Cleanliness	ISO 4406 (c)	>20/18/15	<u> </u>	16/14/10	<b>1</b> 21/19/13			

Customer Id: SCHSTI Sample No.: USP242820 Lab Number: 05963616 Test Package: IND 2



To manage this report scan the QR code

*To discuss the diagnosis or test data:* Doug Bogart +1 (800)237-1369 x4016 <u>dougb@wearcheckusa.com</u>

*To change component or sample information:* Customer Service +1 1-800-237-1369 <u>customerservice@wearcheck.com</u>



# **RECOMMENDED ACTIONS**

There are no recommended actions for this sample.

# HISTORICAL DIAGNOSIS

### 16 Mar 2023 Diag: Doug Bogart



Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

### 19 Jan 2022 Diag: Doug Bogart

06 Jul 2021 Diag: Doug Bogart



Resample at the next service interval to monitor. All component wear rates are normal. There is a moderate amount of silt (particulates < 14 microns in size) present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



view report

#### VIS DEBRIS



We recommend you service the filters on this component. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.All component wear rates are normal. Moderate concentration of visible dirt/debris present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.





# **OIL ANALYSIS REPORT**

# WHS FRICK NH3 - WH5-BOOSTER 2 OK21020 (S/N S003DFEF1HAD3) Component

**Refrigeration Compressor** 

Fluid JAX CRYOGUARD PLUS 68 (--- GAL)

# DIAGNOSIS

# Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

# Contamination

There is a moderate amount of silt (particulates < 14 microns in size) present in the oil.

# Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		USP242820	USP242821	USP237135
Sample Date		Client Info		27 Sep 2023	16 Mar 2023	19 Jan 2022
Machine Age	hrs	Client Info		0	0	33040
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	Not Changd
Sample Status				ATTENTION	NORMAL	ATTENTION
WEAR METALS		method	limit/base	current	history1	history2
Iron	nnm	ASTM D5185m	>8	0	0	<1
Chromium	ppm	ASTM D5185m	>2	0	0	0
Nickel	ppm	ASTM D5185m	r =	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	<1
Aluminum	ppm	ASTM D5185m	>3	<1	0	0
Lead	nom	ASTM D5185m	>2	0	0	0
Conner	nnm	ASTM D5185m	>8	د د1	0	0
Tin	nnm	ASTM D5185m	>4	0	0	0
Antimony	ppm	ASTM D5185m	~7		0	0
Vanadium	nnm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5105m		0	0	-1
Caulillulli	ррш	ASTIVI DJIOJIII		U	0	<1
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m		0	0	0
Calcium	ppm	ASTM D5185m		0	1	0
Phosphorus	ppm	ASTM D5185m		0	<1	0
Zinc	ppm	ASTM D5185m		0	<1	0
Sulfur	ppm	ASTM D5185m		9	0	206
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<1	<1	0
Sodium	ppm	ASTM D5185m		<1	<1	0
Potassium	ppm	ASTM D5185m	>20	0	0	0
Water	%	ASTM D6304	>0.01	0.001	0.003	0.001
ppm Water	ppm	ASTM D6304	>100	3.2	32.0	12.9
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	<b>A</b> 11408	588	<b>▲</b> 11876
Particles >6µm		ASTM D7647	>2500	<u> </u>	152	<u> </u>
Particles >14µm		ASTM D7647	>320	99	8	80
Particles >21µm		ASTM D7647	>80	9	2	9
Particles >38µm		ASTM D7647	>20	0	0	0
Particles >71µm		ASTM D7647	>4	0	0	0
Oil Cleanliness		ISO 4406 (c)	>20/18/15	<b>A</b> 21/19/14	16/14/10	<b>1</b> /19/13
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	ma KOH/a	ASTM D974		0.013	0.016	0.014

Acid Number (AN)

mg KOH/g ASTM D974

0.016 0.014 Contact/Location: DENNIS LONGSHORE - SCHSTI

Report Id: SCHSTI [WUSCAR] 05963616 (Generated: 10/04/2023 23:21:19) Rev: 1



-Pg 0.01

0.00

250

20

E 150

Nater 100

50

8

7

() 70 0

-73 65

60

5

Mar27/

# **OIL ANALYSIS REPORT**







Contact/Location: DENNIS LONGSHORE - SCHSTI

1406

6661