

## **PROBLEM SUMMARY**

# IRIG-PIP-HPU-2001 IRIG-PIP-HPU-2001 HPU PIPE SHED MODULE Component

Hydraulic System

### MOBIL DTE 10 EXCEL 32 (140 GAL)

### COMPONENT CONDITION SUMMARY



#### RECOMMENDATION

We recommend you service the filters on this component. We recommend an early resample to monitor this condition.

PROBLEMATIC TEST RESULTS							
Sample Status			ABNORMAL	ATTENTION	ABNORMAL		
Particles >4µm	ASTM D7647	>2500	<u> </u>	<b>A</b> 3351	▲ 5673		
Particles >6µm	ASTM D7647	>640	<b>4573</b>	183	330		
Particles >14µm	ASTM D7647	>80	🔺 161	6	10		
Oil Cleanliness	ISO 4406 (c)	>18/16/13	<b>A</b> 21/19/15	🔺 19/15/10	🔺 20/16/10		

Customer Id: BPEMPU Sample No.: HLC0002803 Lab Number: 05964177 Test Package: IND 2



To manage this report scan the QR code

To discuss the diagnosis or test data: Wes Davis +1 905-569-8600 x223 wesd@wearcheck.ca

To change component or sample information: Customer Service +1 1-800-237-1369 customerservice@wearcheck.com



RECOMMENDED ACTIONS						
Action	Status	Date	Done By	Description		
Change Filter			?	We recommend you service the filters on this component.		
Resample			?	We recommend an early resample to monitor this condition.		

### HISTORICAL DIAGNOSIS



### 08 Sep 2023 Diag: Wes Davis

We recommend you service the filters on this component. Resample at the next service interval to monitor.All component wear rates are normal. There is a light amount of silt (particulates < 14 microns in size) present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



view report

### 29 Jul 2023 Diag: Wes Davis



We recommend you service the filters on this component. We recommend an early resample to monitor this condition.All component wear rates are normal. There is a moderate amount of silt (particulates < 14 microns in size) present in the oil. The system cleanliness is above the acceptable limit for the target ISO 4406 cleanliness code. The AN level is acceptable for this fluid. The oil is still serviceable provided that the contaminant(s) can be reduced to acceptable levels.

### 26 Jun 2023 Diag: Doug Bogart





Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.







### **OIL ANALYSIS REPORT**

### Area IRIG [6076665] IRIG-PIP-HPU-2001 IRIG-PIP-HPU-2001 HPU PIPE SHED MODULE Component

Hydraulic System

MOBIL DTE 10 EXCEL 32 (140 GAL)

### DIAGNOSIS

#### Recommendation

We recommend you service the filters on this component. We recommend an early resample to monitor this condition.

### Wear

All component wear rates are normal.

### Contamination

There is a moderate amount of silt (particulates < 14 microns in size) present in the oil. The system cleanliness is above the acceptable limit for the target ISO 4406 cleanliness code.

### Fluid Condition

The AN level is acceptable for this fluid. The oil is still serviceable provided that the contaminant(s) can be reduced to acceptable levels.



SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		HLC0002803	HLC0002824	HLC0002698
Sample Date		Client Info		16 Sep 2023	08 Sep 2023	29 Jul 2023
Machine Age	hrs	Client Info		4124	4117	4033
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	Filtered	N/A
Sample Status				ABNORMAL	ATTENTION	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	3	3	3
Chromium	ppm	ASTM D5185m	>20	0	0	0
Nickel	ppm	ASTM D5185m	>20	0	0	<1
Titanium	ppm	ASTM D5185m		0	<1	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>20	0	<1	0
Lead	ppm	ASTM D5185m	>20	0	0	0
Copper	ppm	ASTM D5185m	>20	3	3	3
Tin	ppm	ASTM D5185m	>20	0	0	0
Vanadium	ppm	ASTM D5185m		0	<1	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		<1	<1	0
Magnesium	ppm	ASTM D5185m		0	0	0
Calcium	ppm	ASTM D5185m	120	92	102	90
Phosphorus	ppm	ASTM D5185m	475	449	477	424
Zinc	ppm	ASTM D5185m	4.075	23	0	32
Sulfur	ppm	ASTM D5185m	1275	1351	1651	1387
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<1	<1	<1
Sodium	ppm	ASTM D5185m		3	4	0
Potassium	ppm	ASTM D5185m	>20	3	1	2
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>2500	<b>A</b> 19570	<b>A</b> 3351	<b>6</b> 5673
Particles >6µm		ASTM D7647	>640	<u> </u>	183	330
Particles >14µm		ASTM D7647	>80	<u> </u>	6	10
Particles >21µm		ASTM D7647	>20	28	2	2
Particles >38µm		ASTM D7647	>4	1	0	0
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>18/16/13	<b>21/19/15</b>	▲ 19/15/10	20/16/10
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	ma KOH/a	ASTM D8045		0 187	0 182	0.06



## **OIL ANALYSIS REPORT**







Feb6/77

en5/71

30 Ab

21

26

Viar27/20

ug15/20

Mav9/21

VISUAL		method	limit/base	current	nistory i	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	32	32.3	31.7	34.6
SAMPLE IMAGES		method	limit/base	current	history1	history2

Color

1

(

1



Bottom

### GRAPHS



Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Certificate L2367

Contact/Location: Evan Reilly - BPEMPU

F: x: