



KAESER SFC-18 2182574 (S/N 1008)

Compressor

KAESER SIGMA (OEM) S-460 (--- LTR)

COMPONENT CONDITION SUMMARY



RECOMMENDATION

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

PROBLEMATIC TEST RESULTS								
Sample Status			ABNORMAL	ABNORMAL	ABNORMAL			
Particles >6µm	ASTM D7647	>1300	<u> </u>					
Particles >14µm	ASTM D7647	>80	A 364					
Particles >21µm	ASTM D7647	>20	<u> </u>					
Oil Cleanliness	ISO 4406 (c)	>/17/13	/ 19/18/16					

Customer Id: TENBAL Sample No.: KCPA006263 Lab Number: 05964185 Test Package: IND 2



To manage this report scan the QR code

To discuss the diagnosis or test data: Don Baldridge +1 <u>don.b505@comcast.net</u>

To change component or sample information: Customer Service +1 1-800-237-1369 <u>customerservice@wearcheck.com</u>



There are no recommended actions for this sample.

HISTORICAL DIAGNOSIS





No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.All component wear rates are normal. Moderate concentration of visible dirt/debris present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



view report

04 Oct 2021 Diag: Don Baldridge



No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.All component wear rates are normal. Moderate concentration of visible dirt/debris present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



15 Apr 2021 Diag: Don Baldridge



Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.









OIL ANALYSIS REPORT

KAESER SFC-18 2182574 (S/N 1008)

Compressor Fluid

KAESER SIGMA (OEM) S-460 (--- LTR)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



SAMPLE INFORM	ATION	method	limit/base	current	history1	nistory2
Sample Number		Client Info		KCPA006263	KCP41026	KCP39092
Sample Date		Client Info		31 Aug 2023	08 Mar 2022	04 Oct 2021
Machine Age	hrs	Client Info		99531	91017	87344
Oil Age	hrs	Client Info		0	3673	5742
Oil Changed		Client Info		N/A	Not Changd	Changed
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
		mothod	limit/bass	ourropt	biotonut	history
WEAR METALS		method	iinii/base	current	nistory i	nistory2
Iron	ppm	ASTM D5185m	>50	0	0	<1
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	<1
Aluminum	ppm	ASTM D5185m	>10	0	0	<1
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m	>50	13	6	15
Tin	ppm	ASTM D5185m	>10	0	0	<1
Antimony	ppm	ASTM D5185m				<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	maa	ASTM D5185m		0	0	16
Barium	mag	ASTM D5185m	90	0	0	0
Molvbdenum	ppm	ASTM D5185m		0	0	0
Manganese	mag	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m	90	2	13	3
Calcium	ppm	ASTM D5185m	2	<1	0	3
Phosphorus	ppm	ASTM D5185m		15	5	6
Zinc	mag	ASTM D5185m		9	33	11
Sulfur	ppm	ASTM D5185m		14601	16486	15154
CONTAMINANTS		method	limit/base	current	history1	history2
				current		
Silicon	ppm	ASTM D5185m	>25	<1	0	0
Sodium	ppm	ASTM D5185m	00	2	9	2
Potassium	ppm	ASTM D5185m	>20	2	0	0
Water	%	ASTM D6304	>0.05	0.004	0.010	0.009
ppm Water	ppm	ASTM D6304	>500	43.1	101.4	91.7
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		4071		
Particles >6µm		ASTM D7647	>1300	<u> </u>		
Particles >14µm		ASTM D7647	>80	A 364		
Particles >21µm		ASTM D7647	>20	<u> </u>		
Particles >38µm		ASTM D7647	>4	4		
Particles >71µm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>/17/13	19/18/16		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
					,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	

Acid Number (AN) mg KOH

mg KOH/g ASTM D8045 0.4

0.37 0.39 0.335

Report Id: TENBAL [WUSCAR] 05964185 (Generated: 10/01/2023 14:07:55) Rev: 1

Contact/Location: P. FULLER - TENBAL



OIL ANALYSIS REPORT







VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	LIGHT	🔺 MODER	🔺 MODER
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	46	43.9	44.2	44.5
SAMPLE IMAGES		method	limit/base	current	history1	history2
Color						



Bottom



Contact/Location: P. FULLER - TENBAL