



# PROBLEM SUMMARY

Sample Rating Trend




GLYCOL



Machine Id  
**SZLG232697**  
 Component  
**Diesel Engine**  
 Fluid  
**CHEVRON 15W40 (--- QTS)**

## COMPONENT CONDITION SUMMARY

### ▲ Glycol Contamination



### ▲ Viscosity @ 100°C



## RECOMMENDATION

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

## PROBLEMATIC TEST RESULTS

Sample Status	ATTENTION		---	---		
Sodium	ppm	ASTM D5185m	>50	▲ 110	---	---
Visc @ 100°C	cSt	ASTM D445	14.4	▲ 11.3	---	---

Customer Id: DOLGUL  
 Sample No.: WC0847134  
 Lab Number: 05964467  
 Test Package: FLEET



To manage this report scan the QR code

To discuss the diagnosis or test data:  
 Jonathan Hester +1 919-379-4092 x4092  
[jhester@wearcheckusa.com](mailto:jhester@wearcheckusa.com)

To change component or sample information:  
 Customer Service +1 1-800-237-1369  
[customerservice@wearcheck.com](mailto:customerservice@wearcheck.com)

## RECOMMENDED ACTIONS

Action	Status	Date	Done By	Description
Change Fluid	---	---	?	Oil and filter change at the time of sampling has been noted.
Change Filter	---	---	?	Oil and filter change at the time of sampling has been noted.

## HISTORICAL DIAGNOSIS



# OIL ANALYSIS REPORT

Sample Rating Trend



**GLYCOL**



Machine Id  
**SZLG232697**  
 Component  
**Diesel Engine**  
 Fluid  
**CHEVRON 15W40 (--- QTS)**

## DIAGNOSIS

### ▲ Recommendation

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

Sodium and/or potassium levels are high. Fuel content negligible. Test for glycol is negative.

### ▲ Fluid Condition

The oil viscosity is lower than normal. The BN result indicates that there is suitable alkalinity remaining in the oil. Confirm oil type.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>WC0847134</b>	---	---
Sample Date	Client Info	<b>22 Sep 2023</b>	---	---
Machine Age	hrs	Client Info	<b>1706</b>	---
Oil Age	hrs	Client Info	<b>1706</b>	---
Oil Changed	Client Info	<b>Changed</b>	---	---
Sample Status		<b>ATTENTION</b>	---	---

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	<b>18</b>	---
Chromium	ppm	ASTM D5185m >20	<b>1</b>	---
Nickel	ppm	ASTM D5185m >4	<b>0</b>	---
Titanium	ppm	ASTM D5185m	<b>0</b>	---
Silver	ppm	ASTM D5185m >3	<b>0</b>	---
Aluminum	ppm	ASTM D5185m >20	<b>7</b>	---
Lead	ppm	ASTM D5185m >40	<b>0</b>	---
Copper	ppm	ASTM D5185m >330	<b>8</b>	---
Tin	ppm	ASTM D5185m >15	<b>&lt;1</b>	---
Vanadium	ppm	ASTM D5185m	<b>0</b>	---
Cadmium	ppm	ASTM D5185m	<b>0</b>	---

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	<b>94</b>	---
Barium	ppm	ASTM D5185m	<b>0</b>	---
Molybdenum	ppm	ASTM D5185m	<b>61</b>	---
Manganese	ppm	ASTM D5185m	<b>1</b>	---
Magnesium	ppm	ASTM D5185m	<b>341</b>	---
Calcium	ppm	ASTM D5185m	<b>1836</b>	---
Phosphorus	ppm	ASTM D5185m	<b>963</b>	---
Zinc	ppm	ASTM D5185m	<b>1198</b>	---
Sulfur	ppm	ASTM D5185m	<b>3676</b>	---

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>7</b>	---
Sodium	ppm	ASTM D5185m >50	<b>▲ 110</b>	---
Potassium	ppm	ASTM D5185m >20	<b>3</b>	---
Fuel	%	ASTM D3524 >5	<b>1.9</b>	---
Glycol	%	*ASTM D2982	<b>NEG</b>	---

## INFRA-RED





method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>0.1</b>	---
Nitration	Abs/cm	*ASTM D7624 >20	<b>8.4</b>	---
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>20.2</b>	---

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>18.1</b>	---
Base Number (BN)	mg KOH/g	ASTM D2896	<b>8.7</b>	---







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2	
White Metal	scalar	*Visual	NONE	NONE	---	---
Yellow Metal	scalar	*Visual	NONE	NONE	---	---
Precipitate	scalar	*Visual	NONE	NONE	---	---
Silt	scalar	*Visual	NONE	NONE	---	---
Debris	scalar	*Visual	NONE	NONE	---	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---	---
Appearance	scalar	*Visual	NORML	NORML	---	---
Odor	scalar	*Visual	NORML	NORML	---	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---	---
Free Water	scalar	*Visual		NEG	---	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	14.4	▲ 11.3	---	---

### GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : WC0847134 **Received** : 29 Sep 2023  
**Lab Number** : 05964467 **Diagnosed** : 03 Oct 2023  
**Unique Number** : 10671018 **Diagnostician** : Jonathan Hester  
**Test Package** : FLEET ( Additional Tests: FuelDilution, Glycol, PercentFuel )

**DOLE FRESH FRUIT**  
 PO BOX 1689  
 GULFPORT, MS  
 US 39502  
 Contact: JORDAN JOHNSTON  
 jordan.johnston@dole.com  
 T:  
 F: (228)867-2970

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)