



# PROBLEM SUMMARY

Sample Rating Trend




ISO



Machine Id  
**TAN TAN**  
 Component  
**Lube System**  
 Fluid  
**NOT GIVEN (--- GAL)**

## COMPONENT CONDITION SUMMARY

### ▲ Particle Trend



## RECOMMENDATION

No corrective action is recommended at this time.  
 Resample at the next service interval to monitor.  
 Please specify the brand, type, and viscosity of the oil on your next sample.

## PROBLEMATIC TEST RESULTS

Sample Status				<b>ATTENTION</b>	---	---
Particles >4µm	ASTM D7647	>5000	▲ <b>6202</b>	---	---	---
Particles >6µm	ASTM D7647	>1300	▲ <b>1718</b>	---	---	---
Oil Cleanliness	ISO 4406 (c)	>19/17/14	▲ <b>20/18/14</b>	---	---	---

**Customer Id:** TESAUSTLC  
**Sample No.:** TLC05964593  
**Lab Number:** 05964593  
**Test Package:** PLANT



To manage this report scan the QR code

To discuss the diagnosis or test data:  
 Don Baldrige +1  
[don.b505@comcast.net](mailto:don.b505@comcast.net)

To change component or sample information:  
 Customer Service +1 1-800-237-1369  
[customerservice@wearcheck.com](mailto:customerservice@wearcheck.com)

## RECOMMENDED ACTIONS

Action	Status	Date	Done By	Description
Information Required	---	---	?	Please specify the brand, type, and viscosity of the oil on your next sample.

## HISTORICAL DIAGNOSIS



# OIL ANALYSIS REPORT

Sample Rating Trend



ISO



Machine Id  
**TAN TAN**  
 Component  
**Lube System**  
 Fluid  
**NOT GIVEN (--- GAL)**

## DIAGNOSIS

### Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

### Wear

All component wear rates are normal.

### Contamination

There is a moderate amount of silt (particulates < 14 microns in size) present in the oil.

### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>TLC05964593</b>	---	---
Sample Date	Client Info	<b>19 Sep 2023</b>	---	---
Machine Age	hrs	Client Info	<b>0</b>	---
Oil Age	hrs	Client Info	<b>0</b>	---
Oil Changed	Client Info	<b>N/A</b>	---	---
Sample Status		<b>ATTENTION</b>	---	---

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >20	<b>2</b>	---
Chromium	ppm	ASTM D5185m >20	<b>0</b>	---
Nickel	ppm	ASTM D5185m >20	<b>0</b>	---
Titanium	ppm	ASTM D5185m	<b>0</b>	---
Silver	ppm	ASTM D5185m	<b>0</b>	---
Aluminum	ppm	ASTM D5185m >20	<b>0</b>	---
Lead	ppm	ASTM D5185m >20	<b>2</b>	---
Copper	ppm	ASTM D5185m >20	<b>14</b>	---
Tin	ppm	ASTM D5185m >20	<b>&lt;1</b>	---
Vanadium	ppm	ASTM D5185m	<b>0</b>	---
Cadmium	ppm	ASTM D5185m	<b>0</b>	---

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	<b>0</b>	---
Barium	ppm	ASTM D5185m	<b>&lt;1</b>	---
Molybdenum	ppm	ASTM D5185m	<b>0</b>	---
Manganese	ppm	ASTM D5185m	<b>0</b>	---
Magnesium	ppm	ASTM D5185m	<b>7</b>	---
Calcium	ppm	ASTM D5185m	<b>23</b>	---
Phosphorus	ppm	ASTM D5185m	<b>194</b>	---
Zinc	ppm	ASTM D5185m	<b>23</b>	---
Sulfur	ppm	ASTM D5185m	<b>5899</b>	---

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >15	<b>&lt;1</b>	---
Sodium	ppm	ASTM D5185m	<b>1</b>	---
Potassium	ppm	ASTM D5185m >20	<b>0</b>	---

## FLUID CLEANLINESS

method	limit/base	current	history1	history2
Particles >4µm	ASTM D7647 >5000	<b>▲ 6202</b>	---	---
Particles >6µm	ASTM D7647 >1300	<b>▲ 1718</b>	---	---
Particles >14µm	ASTM D7647 >160	<b>132</b>	---	---
Particles >21µm	ASTM D7647 >40	<b>32</b>	---	---
Particles >38µm	ASTM D7647 >10	<b>0</b>	---	---
Particles >71µm	ASTM D7647 >3	<b>0</b>	---	---
Oil Cleanliness	ISO 4406 (c) >19/17/14	<b>▲ 20/18/14</b>	---	---


## FLUID DEGRADATION

method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	<b>0.19</b>	---




# OIL ANALYSIS REPORT


## ▲ Particle Trend




## ▲ Particle Trend



## Acid Number



## Viscosity @ 40°C



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.05	NEG	---
Free Water	scalar	*Visual		NEG	---


FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	113	---	---

## SAMPLE IMAGES


method	limit/base	current	history1	history2
Color				no image
Bottom				no image

## GRAPHS


### Ferrous Alloys




### Non-ferrous Metals




### Viscosity @ 40°C



### ▲ Particle Count



### Acid Number



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : TLC05964593 **Received** : 29 Sep 2023  
**Lab Number** : 05964593 **Diagnosed** : 02 Oct 2023  
**Unique Number** : 10671144 **Diagnostician** : Don Baldrige  
**Test Package** : PLANT

**TESLA**  
 1 Tesla Road, BIW E58  
 Austin, TX  
 US 78725  
 Contact: Dave Mitchell  
 davmitchell@tesla.com  
 T: (260)226-1968  
 F:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)