

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

GUAY SON [CONHER] Machine Id IBACO BM DAGIO I

Component **Bottom Main Engine**

XTRA REV 15W40 (--- LTR)

Bottom Main Engine

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.



Sample Number Client Info XL0012862 XL0011408 XL0009207	O/MINI LE IIVI OTM	<i>I</i> / 111011	memod	IIIIII/ basc	Carront	Thistory	HISTOTYZ
Machine Age hrs Client Info 13298 13297 0 Oil Age hrs Client Info 1 176 0 Oil Changed Client Info Not Changd N/A Sample Status Image: Client Info Not Changd N/A ATTENTION NORMAL ATTENTION NORMAL CONTAMINATION method limit/base current history1 history2 Fuel WC Method VC Method NEG NEG NEG WEAR METALS method limit/base current history1 history2 Iron ppm ASTM D5185m >75 3 7 44 Chromium ppm ASTM D5185m >2 0 0 <1 Nickel ppm ASTM D5185m >2 0 0 <1 Silver ppm ASTM D5185m >15 3 <1 3 Lead ppm ASTM D5185m >18 0 0	Sample Number		Client Info		KL0012862	KL0011408	KL0009207
Oil Age hrs Client Info Not Changd Not Changd N/A Sample Status Northand Northand Northand N/A CONTAMINATION method limit/base current history1 history2 Fuel WC Method >4.0 <1.0	Sample Date		Client Info		21 Sep 2023	30 Mar 2023	23 Mar 2022
Oil Changed Sample Status	Machine Age	hrs	Client Info		13298	13297	0
Sample Status	Oil Age	hrs	Client Info		1	176	0
CONTAMINATION method limit/base current history2 Fuel WC Method >4.0 <1.0 <1.0 <1.0 Glycol WC Method NEG NEG NEG WEAR METALS method limit/base current history1 history2 Iron ppm ASTM D5185m >75 3 7 44 Chromium ppm ASTM D5185m >8 0 0 1 Nickel ppm ASTM D5185m >2 0 0 <1 Nickel ppm ASTM D5185m >2 0 0 <1 Silver ppm ASTM D5185m >2 0 0 <1 Aluminum ppm ASTM D5185m >15 3 <1 3 <1 3 Lead ppm ASTM D5185m >18 0 0 2 2 Antimony ppm ASTM D5185m >14 <1 0 2	Oil Changed		Client Info		Not Changd	Not Changd	N/A
Fuel	Sample Status				NORMAL	ATTENTION	NORMAL
Fuel	CONTAMINATION	J	method	limit/hase	current	history1	history2
WEAR METALS		•					
WEAR METALS method limit/base current history1 history2 Iron ppm ASTM D5185m >75 3 7 44 Chromium ppm ASTM D5185m >8 0 0 1 Nickel ppm ASTM D5185m >2 0 0 <1 Titanium ppm ASTM D5185m >2 0 0 <1 Aluminum ppm ASTM D5185m >2 0 0 <1 Aluminum ppm ASTM D5185m >18 0 0 2 Copper ppm ASTM D5185m >18 0 0 2 Copper ppm ASTM D5185m >80 <1 <1 4 Tin ppm ASTM D5185m >14 <1 0 2 Antimony ppm ASTM D5185m <1 0 0 0 Vanadium ppm ASTM D5185m <1 0 0				>4.0			
Iron			VVC IVIELLIOU		NEG	NEG	NEG
Chromium ppm ASTM D5185m >8 0 0 1 Nickel ppm ASTM D5185m >2 0 0 <1 Titanium ppm ASTM D5185m >3 <1 0 0 Silver ppm ASTM D5185m >2 0 0 <1 Aluminum ppm ASTM D5185m >15 3 <1 3 Lead ppm ASTM D5185m >18 0 0 2 Copper ppm ASTM D5185m >18 0 0 2 Tin ppm ASTM D5185m >80 <1 <1 4 Tin ppm ASTM D5185m >14 <1 0 2 Antimony ppm ASTM D5185m <1 0 0 0 Caddium ppm ASTM D5185m <1 0 0 0 Cadmium ppm ASTM D5185m 0 0 0 0	WEAR METALS		method	limit/base	current	history1	history2
Nickel ppm ASTM D5185m >2 0 0 <1	Iron	ppm	ASTM D5185m	>75	3	7	44
Titanium	Chromium	ppm	ASTM D5185m	>8	0	0	1
Silver ppm ASTM D5185m >2 0 0 <1	Nickel	ppm	ASTM D5185m	>2	0	0	<1
Aluminum	Titanium	ppm	ASTM D5185m	>3	<1	0	0
Lead	Silver	ppm	ASTM D5185m	>2	0	0	<1
Copper ppm ASTM D5185m >80 <1	Aluminum	ppm	ASTM D5185m	>15	3	<1	3
Tin ppm ASTM D5185m >14 <1	Lead	ppm	ASTM D5185m	>18	0	0	2
Antimony ppm ASTM D5185m	Copper	ppm	ASTM D5185m	>80	<1	<1	4
Vanadium ppm ASTM D5185m <1	Tin	ppm	ASTM D5185m	>14	<1	0	2
Cadmium ppm ASTM D5185m 0 0 0 ADDITIVES method limit/base current history1 history2 Boron ppm ASTM D5185m 22 291 125 Barium ppm ASTM D5185m 0 0 0 Molybdenum ppm ASTM D5185m 8 104 121 Manganese ppm ASTM D5185m -1 <1 <1 Magnesium ppm ASTM D5185m 43 464 595 Calcium ppm ASTM D5185m 2428 1614 1634 Phosphorus ppm ASTM D5185m 1068 844 895 Zinc ppm ASTM D5185m 1306 1069 1053 Sulfur ppm ASTM D5185m 3739 4200 2856 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 <t< th=""><th>Antimony</th><th>ppm</th><th>ASTM D5185m</th><th></th><th></th><th></th><th></th></t<>	Antimony	ppm	ASTM D5185m				
ADDITIVES method limit/base current history1 history2 Boron ppm ASTM D5185m 22 291 125 Barium ppm ASTM D5185m 0 0 0 Molybdenum ppm ASTM D5185m 8 104 121 Manganese ppm ASTM D5185m -1 -1 -1 Magnesium ppm ASTM D5185m 43 464 595 Calcium ppm ASTM D5185m 2428 1614 1634 Phosphorus ppm ASTM D5185m 1068 844 895 Zinc ppm ASTM D5185m 1306 1069 1053 Sulfur ppm ASTM D5185m 3739 4200 2856 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 7 7 11 Soot wh ppm ASTM D5185m >20	Vanadium	ppm	ASTM D5185m		<1	0	0
Boron ppm ASTM D5185m 22 291 125 Barium ppm ASTM D5185m 0 0 0 Molybdenum ppm ASTM D5185m 8 104 121 Manganese ppm ASTM D5185m <1	Cadmium	ppm	ASTM D5185m		0	0	0
Barium ppm ASTM D5185m 0 0 0 Molybdenum ppm ASTM D5185m 8 104 121 Manganese ppm ASTM D5185m <1 <1 <1 Magnesium ppm ASTM D5185m 43 464 595 Calcium ppm ASTM D5185m 2428 1614 1634 Phosphorus ppm ASTM D5185m 1068 844 895 Zinc ppm ASTM D5185m 1306 1069 1053 Sulfur ppm ASTM D5185m 3739 4200 2856 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 7 7 11 Sodium ppm ASTM D5185m >20 2 1 0 INFRA-RED method limit/base current history1 history2 Soot % % *ASTM D7844<	ADDITIVES		method	limit/base	current	history1	history2
Molybdenum ppm ASTM D5185m 8 104 121 Manganese ppm ASTM D5185m <1	Boron	ppm	ASTM D5185m		22	291	125
Manganese ppm ASTM D5185m <1	Barium	ppm	ASTM D5185m		0	0	0
Magnesium ppm ASTM D5185m 43 464 595 Calcium ppm ASTM D5185m 2428 1614 1634 Phosphorus ppm ASTM D5185m 1068 844 895 Zinc ppm ASTM D5185m 1306 1069 1053 Sulfur ppm ASTM D5185m 3739 4200 2856 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 7 7 11 Sodium ppm ASTM D5185m >75 <1 0 8 Potassium ppm ASTM D5185m >20 2 1 0 INFRA-RED method limit/base current history1 history2 Soot % % *ASTM D7844 0.1 0.6 1.9 Nitration Abs/cm *ASTM D7624 >20 4.3 6.4 13.5	Molybdenum	ppm	ASTM D5185m		8	104	121
Calcium ppm ASTM D5185m 2428 1614 1634 Phosphorus ppm ASTM D5185m 1068 844 895 Zinc ppm ASTM D5185m 1306 1069 1053 Sulfur ppm ASTM D5185m 3739 4200 2856 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 7 7 11 Sodium ppm ASTM D5185m >75 <1 0 8 Potassium ppm ASTM D5185m >20 2 1 0 INFRA-RED method limit/base current history1 history2 Soot % % *ASTM D7844 0.1 0.6 1.9 Nitration Abs/cm *ASTM D7624 >20 4.3 6.4 13.5	Manganese	ppm	ASTM D5185m		<1	<1	<1
Phosphorus ppm ASTM D5185m 1068 844 895 Zinc ppm ASTM D5185m 1306 1069 1053 Sulfur ppm ASTM D5185m 3739 4200 2856 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 7 7 11 Sodium ppm ASTM D5185m >75 <1 0 8 Potassium ppm ASTM D5185m >20 2 1 0 INFRA-RED method limit/base current history1 history2 Soot % % *ASTM D7844 0.1 0.6 1.9 Nitration Abs/cm *ASTM D7624 >20 4.3 6.4 13.5	Magnesium	ppm	ASTM D5185m		43	464	595
Zinc ppm ASTM D5185m 1306 1069 1053 Sulfur ppm ASTM D5185m 3739 4200 2856 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 7 7 11 Sodium ppm ASTM D5185m >75 <1 0 8 Potassium ppm ASTM D5185m >20 2 1 0 INFRA-RED method limit/base current history1 history2 Soot % % *ASTM D7844 0.1 0.6 1.9 Nitration Abs/cm *ASTM D7624 >20 4.3 6.4 13.5	Calcium	ppm	ASTM D5185m		2428	1614	1634
Zinc ppm ASTM D5185m 1306 1069 1053 Sulfur ppm ASTM D5185m 3739 4200 2856 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 7 7 11 Sodium ppm ASTM D5185m >75 <1 0 8 Potassium ppm ASTM D5185m >20 2 1 0 INFRA-RED method limit/base current history1 history2 Soot % % *ASTM D7844 0.1 0.6 1.9 Nitration Abs/cm *ASTM D7624 >20 4.3 6.4 13.5	Phosphorus	ppm	ASTM D5185m		1068	844	895
CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 7 7 11 Sodium ppm ASTM D5185m >75 <1 0 8 Potassium ppm ASTM D5185m >20 2 1 0 INFRA-RED method limit/base current history1 history2 Soot % % *ASTM D7844 0.1 0.6 1.9 Nitration Abs/cm *ASTM D7624 >20 4.3 6.4 13.5			ASTM D5185m		1306	1069	1053
Silicon ppm ASTM D5185m >20 7 7 11 Sodium ppm ASTM D5185m >75 <1	Sulfur		ASTM D5185m			4200	2856
Sodium ppm ASTM D5185m >75 <1	CONTAMINANTS		method	limit/base	current	history1	history2
Potassium ppm ASTM D5185m >20 2 1 0 INFRA-RED method limit/base current history1 history2 Soot % % *ASTM D7844 0.1 0.6 1.9 Nitration Abs/cm *ASTM D7624 >20 4.3 6.4 13.5	Silicon	ppm	ASTM D5185m	>20	7	7	11
INFRA-RED method limit/base current history1 history2 Soot % % *ASTM D7844 0.1 0.6 1.9 Nitration Abs/cm *ASTM D7624 >20 4.3 6.4 13.5	Sodium	ppm	ASTM D5185m	>75	<1	0	8
Soot % % *ASTM D7844 0.1 0.6 1.9 Nitration Abs/cm *ASTM D7624 >20 4.3 6.4 13.5	Potassium	ppm	ASTM D5185m	>20	2	1	0
Nitration Abs/cm *ASTM D7624 >20 4.3 6.4 13.5	INFRA-RED		method	limit/base	current	history1	history2
Nitration Abs/cm *ASTM D7624 >20 4.3 6.4 13.5	Soot %	%	*ASTM D7844		0.1	0.6	1.9
		Abs/cm	*ASTM D7624	>20			
	Sulfation	Abs/.1mm		>30			30.2



OIL ANALYSIS REPORT







Certificate L2367

Laboratory Sample No. Lab Number **Unique Number**

: KL0012862 : 05964784

: 10671335

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : 29 Sep 2023 Received Diagnosed : 03 Oct 2023

Sase 0.0

Diagnostician : Angela Borella Test Package : MOB 2 (Additional Tests: PrtCount)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

CONOR JUAREZ 348 HERMOSILLO. MX 83140

Contact: EDUARDO GARCIA egarcia.comsa@gmail.com

T: (526)622-1581 x:81

F: x: