

OIL ANALYSIS REPORT

KIOTI DK5510 47010 (S/N WP8700036)

Diesel Engine

NOT GIVEN (--- GAL)

Sample Rating Trend



Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

				Sep 2023		
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KT0000571		
Sample Date		Client Info		26 Sep 2023		
Machine Age	hrs	Client Info		76		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0		
Glycol		WC Method		NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	69		
Chromium	ppm	ASTM D5185m	>20	<1		
Nickel	ppm	ASTM D5185m	>4	7		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m	>3	0		
Aluminum	ppm	ASTM D5185m	>20	44		
Lead	ppm	ASTM D5185m	>40	12		
Copper	ppm	ASTM D5185m	>330	172		
Tin	ppm	ASTM D5185m	>15	14		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		9		
Barium	ppm	ASTM D5185m		<1		
Molybdenum	ppm	ASTM D5185m		71		
Manganese	ppm	ASTM D5185m		1		
Magnesium	ppm	ASTM D5185m		1094		
Calcium	ppm	ASTM D5185m		1335		
Phosphorus	ppm	ASTM D5185m		1224		
Zinc	ppm	ASTM D5185m		1473		
Sulfur	ppm	ASTM D5185m		2294		
CONTAMINANT	S	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	19		
Sodium	ppm	ASTM D5185m		2		
Potassium	ppm	ASTM D5185m	>20	0		
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.1		
Nitration	Abs/cm	*ASTM D7624	>20	6.9		
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.3		
FLUID DEGRAD	ATION	method	limit/base	current	history1	history2
Oxidation						
Oxidation	Abs/.1mm	*ASTM D7414	>25	17.1		
Base Number (BN)	Abs/.1mm mg KOH/g	*ASTM D7414 ASTM D2896	>25	17.1 7.0		




OIL ANALYSIS REPORT



VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.2	NEG		
Free Water	scalar	*Visual		NEG		
FLUID PROPERT	TIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445		15.2		
GRAPHS						

Pensky-Martens Flash Point (°C)





Laboratory Sample No. Lab Number **Unique Number**

: KT0000571 : 05965227

: 10671778

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 29 Sep 2023 Diagnosed : 03 Oct 2023

Diagnostician : Jonathan Hester

SNYDERS TRACTOR AND EQUIPMENT

174 CRABTREE RD CROSSVILLE, TN US 38571

Test Package : DF-2 (Additional Tests: API, CC Flash, Cetane, Color-ASTM, FT-IR, Fuel, GC-PercFuel, ICP, KF, KV060ntact: HEATH RANDOLPH

To discuss this sample report, contact Customer Service at 1-800-237-1369.

heath.randolph@snyderstractor.com T:

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: