


OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL


Area
[W46757]
 Machine Id
JOHN DEERE 755K 1T0755KXLNF427051
 Component
Transmission (Manual)
 Fluid
JOHN DEERE HYDRAU (--- GAL)


DIAGNOSIS
Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.

Fluid Condition

The condition of the fluid is acceptable for the time in service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		JR0165787	JR0165055	---
Sample Date	Client Info		26 Sep 2023	25 May 2023	---
Machine Age	hrs	Client Info	1005	474	---
Oil Age	hrs	Client Info	0	0	---
Oil Changed	Client Info		Not Chngd	Not Chngd	---
Sample Status			NORMAL	NORMAL	---

WEAR METALS

	method	limit/base	current	history1	history2
PQ	ASTM D8184	>95	14	15	---
Iron	ppm	ASTM D5185m	>200	12	10
Chromium	ppm	ASTM D5185m	>5	0	0
Nickel	ppm	ASTM D5185m	>5	0	<1
Titanium	ppm	ASTM D5185m		0	0
Silver	ppm	ASTM D5185m	>7	0	0
Aluminum	ppm	ASTM D5185m	>25	4	0
Lead	ppm	ASTM D5185m	>45	<1	0
Copper	ppm	ASTM D5185m	>225	7	5
Tin	ppm	ASTM D5185m	>10	0	0
Vanadium	ppm	ASTM D5185m		0	0
Cadmium	ppm	ASTM D5185m		0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0
Barium	ppm	ASTM D5185m		0	0
Molybdenum	ppm	ASTM D5185m		0	<1
Manganese	ppm	ASTM D5185m		0	<1
Magnesium	ppm	ASTM D5185m		4	1
Calcium	ppm	ASTM D5185m	87	93	101
Phosphorus	ppm	ASTM D5185m	727	652	706
Zinc	ppm	ASTM D5185m	900	901	914
Sulfur	ppm	ASTM D5185m	1500	1713	2078



CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>125	1	1
Sodium	ppm	ASTM D5185m		0	<1
Potassium	ppm	ASTM D5185m	>20	0	2

VISUAL

	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG





OIL ANALYSIS REPORT



FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445 65	55.9	57.5	---

SAMPLE IMAGES	method	limit/base	current	history1	history2
Color				no image	no image
Bottom				no image	no image

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : JR0165787 **Received** : 29 Sep 2023
Lab Number : 05965583 **Diagnosed** : 02 Oct 2023
Unique Number : 10672134 **Diagnostician** : Don Baldrige
Test Package : CONST (Additional Tests: PQ)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

JRE - ASHLAND
 11047 LEADBETTER RD
 ASHLAND, VA
 US 23005
 Contact: DAVID ZIEG
 dzieg@jamesriverequipment.com
 T: (804)798-6001
 F: (804)798-0292