


## **OIL ANALYSIS REPORT**

#### **Sample Rating Trend**



NORMAL



# INTERNATIONAL 5016028

Component

**Diesel Engine** 

**DIESEL ENGINE OIL SAE 40 (--- GAL)** 

#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil


### **Fluid Condition**


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

1m2/02/0 Mm2/02/0 Dm2/02/0 Mm2/02/1 Jul2/02/1 Jm2/02/2 Jul2/02/2 Jm2/02/3 Jun2/02/3							
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2	
Sample Number		Client Info		IL05966153	IL05887232	IL05815165	
Sample Date		Client Info		20 Sep 2023	29 Jun 2023	31 Mar 2023	
Machine Age	mls	Client Info		269722	248896	237878	
Oil Age	mls	Client Info		0	0	0	
Oil Changed		Client Info		N/A	N/A	N/A	
Sample Status				NORMAL	NORMAL	NORMAL	
CONTAMINATIO	V	method	limit/base	current	history1	history2	
Fuel		WC Method	>5	<1.0	<1.0	<1.0	
Glycol		WC Method		NEG	NEG	NEG	
WEAR METALS		method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m	>100	54	17	17	
Chromium	ppm	ASTM D5185m	>20	1	<1	0	
Nickel	ppm	ASTM D5185m	>4	<1	<1	0	
Titanium	ppm	ASTM D5185m		<1	<1	<1	
Silver	ppm	ASTM D5185m	>3	0	0	0	
Aluminum	ppm	ASTM D5185m		19	3	4	
Lead	ppm	ASTM D5185m	>40	<1	0	0	
Copper	ppm	ASTM D5185m	>330	5	<1	0	
Tin	ppm	ASTM D5185m	>15	<1	0	0	
Vanadium	ppm	ASTM D5185m		0	<1	0	
Cadmium	ppm	ASTM D5185m		0	0	0	
ADDITIVES		method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m	250	47	127	127	
Barium	ppm	ASTM D5185m	10	0	0	0	
Molybdenum	ppm	ASTM D5185m	100	106	83	81	
Manganese	ppm	ASTM D5185m		2	<1	<1	
Magnesium	ppm	ASTM D5185m	450	777	516	609	
Calcium	ppm	ASTM D5185m	3000	1721	1364	1423	
Phosphorus	ppm	ASTM D5185m	1150	1171	943	908	
Zinc	ppm	ASTM D5185m	1350	1450	1157	1204	
Sulfur	ppm	ASTM D5185m	4250	3237	2924	3172	
CONTAMINANTS		method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m	>25	14	6	5	
Sodium	ppm	ASTM D5185m		7	1	1	
Potassium	ppm	ASTM D5185m	>20	10	4	1	
INFRA-RED		method	limit/base	current	history1	history2	
Soot %	%	*ASTM D7844	>3	1.7	0.5	0.5	
Nitration	Abs/cm	*ASTM D7624	>20	13.2	10.4	10.4	
Sulfation	Abs/.1mm	*ASTM D7415	>30	30.1	22.9	22.9	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2	
Oxidation	Abs/.1mm	*ASTM D7414	>25	27.4	18.5	19.3	
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	5.2	6.7	6.6	




## **OIL ANALYSIS REPORT**








VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
<b>Emulsified Water</b>	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG

FLUID PROPER	TIES	method				history2
Visc @ 100°C	cSt	ASTM D445	14.4	13.7	12.6	12.7













Certificate L2367

Laboratory Sample No.

Lab Number **Unique Number** Test Package : FLEET

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : IL05966153 : 05966153 : 10672704

Received Diagnosed

: 02 Oct 2023 : 03 Oct 2023

Diagnostician : Don Baldridge

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) TAMPA IDEALEASE 5951 ORIENT ROAD TAMPA, FL

US 33610-9565 Contact: Russ Cook russcook@idealease.com

> T: (813)626-9285 F: (844)270-1356