

OIL ANALYSIS REPORT

Sample Rating Trend

INSOLUBLES

A

Machine Id

Press #6 Press #6

Component

Hydraulic System

KLUBER KLUBEROIL 4 UH1-46 N (220 GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

MPC (Membrane Patch Colorimetry) test indicates a light concentration of varnish present. The amount and size of particulates present in the system are acceptable.


Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

m2021 May2021 Aug2021 Nov2021 Mar2022 Sapt002 Jan2023 Apr2023 Jan2023 Sap203						
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PTK0004798	PTK0004795	PTK0004614
Sample Date		Client Info		19 Sep 2023	06 Sep 2023	21 Aug 2023
Machine Age	hrs	Client Info		18881	18641	18266
Oil Age	hrs	Client Info		615	375	0
Oil Changed		Client Info		Not Changd	Not Changd	Changed
Sample Status				MARGINAL	MARGINAL	SEVERE
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	3	3	<1
Chromium	ppm	ASTM D5185m	>10	0	<1	<1
Nickel	ppm	ASTM D5185m	>10	<1	0	0
Titanium	ppm	ASTM D5185m		0	<1	<1
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>10	0	<1	0
Lead	ppm	ASTM D5185m	>10	0	0	<1
Copper	ppm	ASTM D5185m	>75	<1	<1	<1
Tin	ppm		>10	0	<1	<1
Vanadium	ppm	ASTM D5185m		0	<1	<1
Cadmium	ppm	ASTM D5185m		0	<1	<1
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		1	<1	6
Calcium	ppm	ASTM D5185m		6	1	0
Phosphorus	ppm	ASTM D5185m		116	127	136
Zinc	ppm	ASTM D5185m		13	12	19
Sulfur	ppm	ASTM D5185m		3	31	0
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	2	2	2
Sodium	ppm	ASTM D5185m		0	1	1
Potassium	ppm	ASTM D5185m	>20	1	4	3
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
FLUID CLEANLIN Particles >4μm	ESS	method ASTM D7647	limit/base >5000	current 134	392	525
	ESS		>5000			
Particles >4μm Particles >6μm Particles >14μm	ESS	ASTM D7647 ASTM D7647 ASTM D7647	>5000 >1300 >160	134 35 6	392 75 9	525 177 17
Particles >4μm Particles >6μm Particles >14μm Particles >21μm	ESS	ASTM D7647 ASTM D7647	>5000 >1300 >160	134 35	392 75	525 177 17 6
Particles >4µm Particles >6µm Particles >14µm Particles >21µm Particles >38µm	ESS	ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>5000 >1300 >160	134 35 6 2	392 75 9 3	525 177 17 6
Particles >4μm Particles >6μm Particles >14μm Particles >21μm	ESS	ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>5000 >1300 >160 >40	134 35 6 2 1	392 75 9	525 177 17 6 0
Particles >4µm Particles >6µm Particles >14µm Particles >21µm Particles >38µm	ESS	ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>5000 >1300 >160 >40 >10	134 35 6 2	392 75 9 3	525 177 17 6
Particles >4µm Particles >6µm Particles >14µm Particles >21µm Particles >38µm Particles >71µm		ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>5000 >1300 >160 >40 >10 >3	134 35 6 2 1	392 75 9 3 0	525 177 17 6 0
Particles >4µm Particles >6µm Particles >14µm Particles >21µm Particles >38µm Particles >71µm Oil Cleanliness		ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647 ISO 4406 (c)	>5000 >1300 >160 >40 >10 >3 >19/17/14	134 35 6 2 1 0 14/12/10	392 75 9 3 0 0 16/13/10	525 177 17 6 0 0 16/15/11



OIL ANALYSIS REPORT




* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F:

T: (909)239-7599





Report Id: NIAPLE [WUSCAR] 05966228 (Generated: 10/17/2023 18:33:57) Rev: 1

This page left intentionally blank