

# **OIL ANALYSIS REPORT**

#### Area Fermentation Machine Id Lightnin FHG52BB01 Seed Fermentor, Agitator Component

**Gearbox** 

JAX FGG-AW ISO 220 (11 GAL)

#### DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

#### Wear


All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

## Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.





SAMPLE INFORM	<b>MATION</b>	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0843013	WC0697842	WC0753880
Sample Date		Client Info		27 Sep 2023	17 Feb 2023	08 Feb 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>200	10	3	45
Chromium	ppm	ASTM D5185m	>15	0	0	0
Nickel	ppm	ASTM D5185m	>15	<1	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	0	0	<1
Lead	ppm	ASTM D5185m	>100	0	0	0
Copper	ppm	ASTM D5185m		0	0	0
Tin	ppm	ASTM D5185m	>25	0	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	<1
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	0	<1
Magnesium	ppm	ASTM D5185m		0	0	0
Calcium	ppm	ASTM D5185m		7	<1	3
Phosphorus	ppm	ASTM D5185m		463	453	486
Zinc	ppm	ASTM D5185m		2	0	5
Sulfur	ppm	ASTM D5185m		716	734	623
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	<1	<1	5
Sodium	ppm	ASTM D5185m		0	0	<1
Potassium	ppm	ASTM D5185m	>20	<1	0	0
Water	%	ASTM D6304	>0.2	0.001	0.010	0.114
ppm Water	ppm	ASTM D6304	>2000	5.9	103.3	1140
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>320000	65945	54833	
Particles >6µm		ASTM D7647	>20000	3054	5005	
Particles >14µm		ASTM D7647	>640	79	410	
Particles >21µm		ASTM D7647	>160	18	118	
Particles >38µm		ASTM D7647	>40	1	4	
Particles >71µm		ASTM D7647	>10	0	0	
Oil Cleanliness		ISO 4406 (c)	>25/21/16	23/19/13	23/20/16	
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.46	0.46	0.70




# **OIL ANALYSIS REPORT**







VISUAL		la a dita an	1:		la la tamut	histow.0
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	VLITE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	LIGHT	A MODER
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	0.2%
Free Water	scalar	*Visual		NEG	NEG	<b>1</b> .0
FI UID PROPERT	IFS	method	limit/base	current	historv1	history2
FLUID PROPERT Visc @ 40°C	TES cSt	method ASTM D445	limit/base 220	current 223	history1 223	history2 227
	cSt					
Visc @ 40°C	cSt	ASTM D445	220	223	223	227



Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: (919)494-3456