

OIL ANALYSIS REPORT


Sample Rating Trend

WEAR

NCRTS SSI 2500 1 H (S/N C1645)

Hydraulic System

AW HYDRAULIC OIL ISO 46 (--- GAL)





DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

The iron level is abnormal. All other component wear rates are normal.

Contamination

There is a high amount of silt (particulates < 6 microns in size) present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

9/2014 Apr/2015 Apr/2017 Onc/2017 Onc/2018 Onc/2018 Jun/2021 Feb.2022						
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		Y2K0000868	Y2K0000848	Y2K0000838
Sample Date		Client Info		26 Sep 2023	26 Jul 2023	18 May 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	1	0	<1
Chromium	ppm	ASTM D5185m	>20	4 1	4 9	△ 34
Nickel	ppm	ASTM D5185m	>20	0	<1	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	<1	0
Aluminum	ppm	ASTM D5185m	>20	1	<1	1
Lead	ppm	ASTM D5185m	>20	0	<1	0
Copper	ppm	ASTM D5185m	>20	16	16	13
Tin	ppm	ASTM D5185m	>20	0	0	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	5	0	0	0
Barium	ppm	ASTM D5185m	5	0	0	0
Molybdenum	ppm	ASTM D5185m	5	0	0	0
Manganese	ppm	ASTM D5185m		0	0	<1
Magnesium	ppm	ASTM D5185m	25	<1	0	0
Calcium	ppm	ASTM D5185m	200	35	35	37
Phosphorus	ppm	ASTM D5185m	300	321	342	326
Zinc	ppm	ASTM D5185m	370	394	416	399
Sulfur	ppm	ASTM D5185m	2500	873	841	929
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	2	3	4
Sodium	ppm	ASTM D5185m		0	<1	1
Potassium	ppm	ASTM D5185m	>20	<1	<1	0
Water	%	ASTM D6304	>0.05	0.003	0.010	0.003
ppm Water	ppm	ASTM D6304	>500	29.3	103.7	25.3
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	<u> </u>	△ 9043	1652
Particles >6µm		ASTM D7647	>1300	62	140	139
Particles >14µm		ASTM D7647	>160	5	11	7
Particles >21µm		ASTM D7647	>40	2	3	1
Particles >38µm		ASTM D7647	>10	0	0	0
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>19/17/14	<u> </u>	<u>^</u> 20/14/11	18/14/10
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2



OIL ANALYSIS REPORT

