

# **OIL ANALYSIS REPORT**

Sample Rating Trend

ISO

## Area **PITT OHIO** Machine Id **PITT OHIO D2680** Component

Rear Differential Fluid NOT GIVEN (--- GAL)

# DIAGNOSIS

## A Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

# Wear

All component wear rates are normal.

# Contamination

There is a high amount of silt (particulates < 14 microns in size) present in the oil.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0853879	WC0828718	
Sample Date		Client Info		20 Sep 2023	22 May 2023	
Machine Age	mls	Client Info		50801	80	
Oil Age	mls	Client Info		0	0	
Oil Changed		Client Info		N/A	N/A	
Sample Status				ABNORMAL	ABNORMAL	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>500	80	7	
Chromium	ppm	ASTM D5185m	>10	<1	0	
Nickel	ppm	ASTM D5185m	>10	<1	0	
Titanium	ppm	ASTM D5185m		0	0	
Silver	ppm	ASTM D5185m		0	0	
Aluminum	ppm	ASTM D5185m	>25	<1	<1	
Lead	ppm	ASTM D5185m	>25	<1	0	
Copper	ppm	ASTM D5185m	>100	1	0	
Tin		ASTM D5185m	>100	י <1	<1	
	ppm		>10	<1		
Vanadium	ppm	ASTM D5185m			<1	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		100	108	
Barium	ppm	ASTM D5185m		0	0	
Molybdenum	ppm	ASTM D5185m		<1	0	
Manganese	ppm	ASTM D5185m		5	<1	
Magnesium	ppm	ASTM D5185m		172	187	
Calcium	ppm	ASTM D5185m		19	<1	
Phosphorus	ppm	ASTM D5185m		1708	1701	
Zinc	ppm	ASTM D5185m		6	0	
Sulfur	ppm	ASTM D5185m		25961	25056	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>75	12	4	
Sodium	ppm	ASTM D5185m		3	<1	
Potassium	ppm	ASTM D5185m	>20	<1	0	
Water	%	ASTM D6304	>.2	0.025	0.031	
ppm Water	ppm	ASTM D6304	>2000	252.1	312.0	
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>20000	<b>A</b> 114151	126731	
Particles >6µm		ASTM D7647	>5000	<u> </u>	▲ 39290	
Particles >14µm		ASTM D7647	>640	47	<b>A</b> 876	
Particles >21µm		ASTM D7647	>160	9	157	
Particles >38μm		ASTM D7647	>40	1	4	
Particles >71µm		ASTM D7647	>10	0	0	
Oil Cleanliness		ISO 4406 (c)	>21/19/16	<u> </u>	A 24/22/17	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.74	0.80	
				<b>v</b> <i>i</i>	0.00	



# **OIL ANALYSIS REPORT**

