

OIL ANALYSIS REPORT

Area [18467] 20-86

Component Swi Fluid

Sample Rating Trend




Swing Drive							
CONOCO PHILLIPS 80W90 (GAL)							
					Sep2023	<u> </u>	
DIAGNOSIS	SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Recommendation	Sample Number		Client Info		WC0818610		
Resample at the next service interval to monitor. (Sample Date		Client Info		08 Sep 2023		
Customer Sample Comment: ConocoPhillips	Machine Age	hrs	Client Info		5866		
80w/90 gear oil)	Oil Age	hrs	Client Info		5567		
Wear	Oil Changed		Client Info		Not Changd		
All component wear rates are normal.	Sample Status				NORMAL		
Contamination There is no indication of any contamination in the	WEAR METALS		method	limit/base	current	history1	history2
oil.	Iron	ppm	ASTM D5185m	>400	31		
Fluid Condition	Chromium	ppm	ASTM D5185m	>10	1		
The condition of the oil is acceptable for the time in	Nickel	ppm	ASTM D5185m	>10	<1		
service.	Titanium	ppm	ASTM D5185m		0		
	Silver	ppm	ASTM D5185m		0		
	Aluminum	ppm	ASTM D5185m	>25	0		
	Lead	ppm	ASTM D5185m	>50	<1		
	Copper	ppm	ASTM D5185m	>200	<1		
	Tin	ppm	ASTM D5185m	>10	0		
	Vanadium	ppm	ASTM D5185m		0		
	Cadmium	ppm	ASTM D5185m		0		
	ADDITIVES		method	limit/base	current	history1	history2
	Boron	ppm	ASTM D5185m		262		
	Barium	ppm	ASTM D5185m		0		
	Molybdenum	ppm	ASTM D5185m		<1		
	Manganese	ppm	ASTM D5185m		2		
	Magnesium	ppm	ASTM D5185m		0		
	Calcium	ppm	ASTM D5185m		15		
	Phosphorus	ppm	ASTM D5185m		983		
					_		

Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>400	31		
Chromium	ppm	ASTM D5185m	>10	1		
Nickel	ppm	ASTM D5185m	>10	<1		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	0		
Lead	ppm	ASTM D5185m	>50	<1		
Copper	ppm	ASTM D5185m	>200	<1		
Tin	ppm	ASTM D5185m	>10	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		262		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		<1		
Manganese	ppm	ASTM D5185m		2		
Magnesium	ppm	ASTM D5185m		0		
Calcium	ppm	ASTM D5185m		15		
Phosphorus	ppm	ASTM D5185m		983		
Zinc	ppm	ASTM D5185m		6		
Sulfur	ppm	ASTM D5185m		20826		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	2		
Sodium	ppm	ASTM D5185m		10		
Potassium	ppm	ASTM D5185m	>20	1		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.2	NEG		
Free Water	scalar	*Visual		NEG		
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445		137		




OIL ANALYSIS REPORT







GRAPHS



Non-ferrous Metals



Viscosity @ 40°C







Certificate L2367

Laboratory Sample No. Lab Number

Unique Number : 10675025

: WC0818610 : 05968474 Test Package : CONST

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 03 Oct 2023 Diagnosed : 04 Oct 2023

Diagnostician : Doug Bogart

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

MANHATTAN ROAD AND BRIDGE

5601 S 122ND E AVE TULSA, OK

US 74146 Contact: JAMES STEELMON

james.steelmon@manhattanrb.com

T: F: