


OIL ANALYSIS REPORT

Sample Rating Trend







F20 Component

Transmission (Auto)

CASTROL TRANSYND 668 (--- GAL)

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.


Fluid Condition

The condition of the fluid is acceptable for the time in service.

| | | | | Oct2023 | | |
|------------------|--------|-------------|------------|-------------|----------|----------|
| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | WC0784022 | | |
| Sample Date | | Client Info | | 03 Oct 2023 | | |
| Machine Age | hrs | Client Info | | 8672 | | |
| Oil Age | hrs | Client Info | | 3370 | | |
| Oil Changed | | Client Info | | Changed | | |
| Sample Status | | | | NORMAL | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >160 | 38 | | |
| Chromium | ppm | ASTM D5185m | >5 | <1 | | |
| Nickel | ppm | ASTM D5185m | >5 | <1 | | |
| Titanium | ppm | ASTM D5185m | | 0 | | |
| Silver | ppm | ASTM D5185m | >5 | 0 | | |
| Aluminum | ppm | ASTM D5185m | >50 | 13 | | |
| Lead | ppm | ASTM D5185m | >50 | 2 | | |
| Copper | ppm | ASTM D5185m | >225 | 24 | | |
| Tin | ppm | ASTM D5185m | >10 | 2 | | |
| Vanadium | ppm | ASTM D5185m | | 0 | | |
| Cadmium | ppm | ASTM D5185m | | 0 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 70 | | |
| Barium | ppm | ASTM D5185m | | 0 | | |
| Molybdenum | ppm | ASTM D5185m | | <1 | | |
| Manganese | ppm | ASTM D5185m | | <1 | | |
| Magnesium | ppm | ASTM D5185m | | 8 | | |
| Calcium | ppm | ASTM D5185m | | 310 | | |
| Phosphorus | ppm | ASTM D5185m | | 290 | | |
| Zinc | ppm | ASTM D5185m | | 8 | | |
| Sulfur | ppm | ASTM D5185m | | 1812 | | |
| CONTAMINANTS | 6 | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >20 | 4 | | |
| Sodium | ppm | ASTM D5185m | | 4 | | |
| Potassium | ppm | ASTM D5185m | >20 | <1 | | |
| VISUAL | | method | limit/base | current | history1 | history2 |
| White Metal | scalar | *Visual | NONE | NONE | | |
| Yellow Metal | scalar | *Visual | NONE | NONE | | |
| Precipitate | scalar | *Visual | NONE | NONE | | |
| Silt | scalar | *Visual | NONE | NONE | | |
| Debris | scalar | *Visual | NONE | NONE | | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | | |
| Appearance | scalar | *Visual | NORML | NORML | | |
| Odor | scalar | *Visual | NORML | NORML | | |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | | |
| Free Water | scalar | *Visual | | NEG | | |
| FLUID PROPERT | ΓIES | method | limit/base | current | history1 | history2 |




OIL ANALYSIS REPORT





| SAMPLE IMA | AGES | method | limit/base | current | history1 | history2 |
|------------|------|--------|------------|----------|----------|----------|
| Color | | | | no image | no image | no image |
| Bottom | | | | no image | no image | no image |

GRAPHS



Non-ferrous Metals









Certificate L2367

Laboratory Sample No. Lab Number Unique Number : 10675048 Test Package : CONST

: WC0784022 : 05968497

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : 03 Oct 2023 Received Diagnosed : 04 Oct 2023

Diagnostician : Doug Bogart

Apple Valley Waste - EHT Location 6626 Delilah Road

Egg Harbor Township, NJ US 08234

Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:

F: