




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
93032
 Component
Diesel Engine
 Fluid
AMERIGUARD 15W40 (10 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			SBP0004981	SBP0002549	SBP0002564
Sample Date	Client Info			13 Sep 2023	03 Apr 2023	01 Feb 2023
Machine Age	mls	Client Info		334525	330108	326506
Oil Age	mls	Client Info		0	3602	17412
Oil Changed	Client Info			N/A	Changed	Changed
Sample Status				NORMAL	NORMAL	SEVERE

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<1.0	<1.0	<1.0
Glycol	WC Method			NEG	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>80	11	14	▲ 123
Chromium	ppm	ASTM D5185m	>5	<1	<1	3
Nickel	ppm	ASTM D5185m	>2	<1	0	▲ 4
Titanium	ppm	ASTM D5185m		0	<1	5
Silver	ppm	ASTM D5185m	>3	<1	0	0
Aluminum	ppm	ASTM D5185m	>30	3	0	▲ 12
Lead	ppm	ASTM D5185m	>30	0	<1	<1
Copper	ppm	ASTM D5185m	>150	1	<1	3
Tin	ppm	ASTM D5185m	>5	<1	0	<1
Antimony	ppm	ASTM D5185m		---	---	---
Vanadium	ppm	ASTM D5185m		0	0	<1
Cadmium	ppm	ASTM D5185m		<1	0	0

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		1	<1	5
Barium	ppm	ASTM D5185m		0	2	2
Molybdenum	ppm	ASTM D5185m		63	61	68
Manganese	ppm	ASTM D5185m		<1	<1	1
Magnesium	ppm	ASTM D5185m		1112	939	1064
Calcium	ppm	ASTM D5185m		1186	1085	1291
Phosphorus	ppm	ASTM D5185m		1204	995	1189
Zinc	ppm	ASTM D5185m		1525	1237	1418
Sulfur	ppm	ASTM D5185m		3789	2989	3171



CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	6	6	● 61
Sodium	ppm	ASTM D5185m		<1	<1	2
Potassium	ppm	ASTM D5185m	>20	2	1	3

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.2	0.3	0.4
Nitration	Abs/cm	*ASTM D7624	>20	6.7	8.1	9.7
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.6	19.7	22.6

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	16.9	19.5	20.2
Base Number (BN)	mg KOH/g	ASTM D2896		9.3	8.1	9.5







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	13.9	14.3	13.0

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : SBP0004981 **Received** : 04 Oct 2023
Lab Number : **05968608** **Diagnosed** : 04 Oct 2023
Unique Number : 10675159 **Diagnostician** : Wes Davis
Test Package : FLEET

Sapp Bros. Fleet - Omaha Petroleum Location
 9915 South 148th
 OMAHA, NE
 US 68138
 Contact: Stephanie Kelly
 skelly@sappbros.net
 T: (800)211-8589
 F:

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)