

## **OIL ANALYSIS REPORT**

# [W46925] JOHN DEERE 850L 1T0850LXKPF437810

Component Left Inner Final Drive

JOHN DEERE HY-GARD HYD/TRANS (--- GAL)

## DIAGNOSIS

## Recommendation

Resample at the next service interval to monitor.

#### Wear

Elui


All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

## Fluid Condition

The condition of the oil is acceptable for the time in service.






NORMAL

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		JR0179352		
Sample Date		Client Info		03 Oct 2023		
Machine Age	hrs	Client Info		946		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184	>1250	70		motory
Iron	ppm	ASTM D5185m	>750	79		
Chromium	ppm	ASTM D5185m	>9	<1		
Nickel	ppm	ASTM D5185m	>10	0		
Titanium	ppm	ASTM D5185m	>10	0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>40	6		
		ASTM D5185m		0		
Lead Copper	ppm	ASTM D5185m	>15 >40	0		
	ppm	ASTM D5185m		0		
Tin	ppm		>10	-		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	6	0		
Barium	ppm	ASTM D5185m	0	0		
Molybdenum	ppm	ASTM D5185m	0	<1		
Manganese	ppm	ASTM D5185m		1		
Magnesium	ppm	ASTM D5185m	145	104		
Calcium	ppm	ASTM D5185m	3570	3616		
Phosphorus	ppm	ASTM D5185m	1290	1146		
Zinc	ppm	ASTM D5185m	1640	1345		
Sulfur	ppm	ASTM D5185m		3824		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>75	5		
Sodium	ppm	ASTM D5185m	>51	1		
Potassium	ppm	ASTM D5185m	>20	0		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.075	NEG		
Free Water	scalar	*Visual		NEG		



# **OIL ANALYSIS REPORT**



	FLUID PROPER Visc @ 40°C		method ASTM D445	limit/base	e current 50.3	history1	history 
	SAMPLE IMAGE		method	limit/base		history1	history
		_0	monou	innibidoc			
	Color				no image	no image	no image
+					ne mage	nomago	ne inage
0ct3/23							
	Bottom				no image	no image	no image
	GRAPHS						
	Ferrous Alloys			13	PQ		
	70 - iron chromium				250 - Abnormal		
	60 -				200		
	50 -				100 -		
	튭 40 -				)50		
	30				950 -		
	20-				900		
		****			800		
	0ct3/23			2	700		
	Non-ferrous Meta			52 (	650 - 600 -		
	<sup>10</sup> T	ais			550 -		
	9 - copper copper 8 - copper 10				500		
	7-				100		
	6- Ē 5-				850		
	4				250 - Smore		
	3-				200		
	1			1	00-		
				23	50 0		
	0ct3/23			0ct3/23	0ct3/23		
	Viscosity @ 40°C	2					
	Q						
	65 -						
	60						
	ු <b>Base</b> දෙ 55 ද						
	50-						
	45 -						
	40						
	0ct3/23			0ct3/23			

Contact/Location: DAVID ZIEG - JAMASH