

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

Area Bernardsville Machine Id WESTERN STAR 1209 Component

Diesel Engine Fluid SHELL ROTELLA T 15W40 (11)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

			Jageoro	0002020		
SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0840484	WC0830839	
Sample Date		Client Info		30 Sep 2023	29 Aug 2023	
Machine Age	hrs	Client Info		9504	156193	
Oil Age	hrs	Client Info		0	9241	
Oil Changed		Client Info		Changed	Changed	
Sample Status				NORMAL	NORMAL	
CONTAMINATIO	N	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0	<1.0	
Glycol		WC Method	20	NEG	NEG	
		_		iied		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	6	9	
Chromium	ppm	ASTM D5185m	>20	<1	<1	
Nickel	ppm	ASTM D5185m	>4	0	0	
Titanium	ppm	ASTM D5185m		<1	0	
Silver	ppm	ASTM D5185m	>3	0	0	
Aluminum	ppm	ASTM D5185m	>20	6	11	
Lead	ppm	ASTM D5185m	>40	<1	0	
Copper	ppm	ASTM D5185m	>330	<1	<1	
Tin	ppm	ASTM D5185m	>15	<1	<1	
Vanadium	ppm	ASTM D5185m		<1	0	
Cadmium	ppm	ASTM D5185m		<1	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	316	33	8	
Barium	ppm	ASTM D5185m	0.0	12	0	
Molybdenum	ppm	ASTM D5185m	1.2	68	58	
Manganese	ppm	ASTM D5185m		<1	<1	
Magnesium	ppm	ASTM D5185m	24	443	813	
Calcium	ppm	ASTM D5185m	2292	1539	1124	
Phosphorus	ppm	ASTM D5185m	1064	943	945	
Zinc	ppm	ASTM D5185m	1160	1133	1134	
Sulfur	ppm	ASTM D5185m	4996	3332	3525	
CONTAMINANTS		method	limit/base	current	history1	history2
				4		
Silicon	ppm	ASTM D5185m	>20	-	3	
Sodium Potassium	ppm	ASTM D5185m ASTM D5185m	> 20	1	2	
Polassium	ppm	ASTIVI DOTIODITI	>20	15	22	
						history2
INFRA-RED		method	limit/base		,	,, ,
INFRA-RED Soot %	%	method *ASTM D7844	>3	0.5	0.7	
	% Abs/cm					
Soot %		*ASTM D7844	>3	0.5	0.7	
Soot % Nitration	Abs/cm Abs/.1mm	*ASTM D7844 *ASTM D7624	>3 >20	0.5 7.3	0.7 7.4	
Soot % Nitration Sulfation FLUID DEGRADA	Abs/cm Abs/.1mm	*ASTM D7844 *ASTM D7624 *ASTM D7415 method	>3 >20 >30 limit/base	0.5 7.3 17.6 current	0.7 7.4 18.9 history1	
Soot % Nitration Sulfation FLUID DEGRADA Oxidation	Abs/cm Abs/.1mm TION Abs/.1mm	*ASTM D7844 *ASTM D7624 *ASTM D7415 method *ASTM D7414	>3 >20 >30 limit/base >25	0.5 7.3 17.6 current 12.2	0.7 7.4 18.9 history1 13.4	 history2
Soot % Nitration Sulfation FLUID DEGRADA	Abs/cm Abs/.1mm	*ASTM D7844 *ASTM D7624 *ASTM D7415 method	>3 >20 >30 limit/base >25	0.5 7.3 17.6 current	0.7 7.4 18.9 history1	 history2



OIL ANALYSIS REPORT





Certificate L2367

Contact/Location: Pablo Chardon - INTBER