


OIL ANALYSIS REPORT

Sample Rating Trend

COOLING TOWER PUMP MOTORS P-752-UPPER

Component Bearing

MOBIL SHC 626 (9 QTS)





Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Dec2019 Ju	2020 Mar2021 Aug2021	Marž022 Sep2022 Apr2023 Jul20	23 Oct2023	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0866657	WC0835520	WC0809600
Sample Date		Client Info		11 Oct 2023	06 Jul 2023	12 Apr 2023
Machine Age	mths	Client Info		0	0	0
Oil Age	mths	Client Info		2	10	7
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	0	0	0
Chromium	ppm	ASTM D5185m	>20	0	0	0
Nickel	ppm	ASTM D5185m	>20	0	0	0
Titanium	ppm	ASTM D5185m		0	<1	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>20	0	<1	0
Lead	ppm	ASTM D5185m	>20	0	0	0
Copper	ppm	ASTM D5185m	>20	0	0	0
Tin	ppm	ASTM D5185m	>20	0	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	0	<1
Magnesium	ppm	ASTM D5185m		0	3	2
Calcium	ppm	ASTM D5185m		0	0	0
Phosphorus	ppm	ASTM D5185m		482	471	435
Zinc	ppm	ASTM D5185m		0	8	0
Sulfur	ppm	ASTM D5185m		9	0	0
CONTAMINANTS	5	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	0	2	<1
Sodium	ppm	ASTM D5185m		<1	<1	0
Potassium	ppm	ASTM D5185m	>20	0	0	0
FLUID CLEANLIN	NESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647	>10000	3863		
Particles >6µm		ASTM D7647	>2500	1145		
Particles >14μm		ASTM D7647	>160	79		
Particles >21µm		ASTM D7647	>40	24		
Particles >38μm		ASTM D7647	>10	1		
Particles >71μm		ASTM D7647	>3	0		
Oil Cleanliness		ISO 4406 (c)	>20/18/14	19/17/13		
FLUID DEGRADA	NOITA	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.42	0.54	0.32



OIL ANALYSIS REPORT







Laboratory Sample No. Lab Number **Unique Number**

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

: 05978881 : 10696176

: WC0866657 Received Diagnosed Diagnostician

: 19 Oct 2023 : Jonathan Hester Test Package : IND 2 (Additional Tests: PrtCount)

: 13 Oct 2023

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

POET BIOREFINING - Groton

40425 133RD STREET GROTON, SD US 57445-6400

Contact: GAVIN KRUEGER Gavin.Krueger@POET.COM T: 6(05)846-6863

F: (605)397-2754