


# **OIL ANALYSIS REPORT**

### Sample



## NORMAL



# MELT SHOP - SGP Machine Id SLAB GRINDER #1 DUST BOX

Component

Gearbox

GEAR OIL ISO 220 (--- QTS)

## DIAGNOSIS

#### Recommendation

Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

#### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		RP0038347	RP0035106	RP0029743
Sample Date		Client Info		13 Oct 2023	11 May 2023	07 Sep 2022
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184		18	12	10
Iron	ppm	ASTM D5185m	>200	2	3	32
Chromium	ppm	ASTM D5185m	>15	0	0	0
Nickel	ppm	ASTM D5185m	>15	0	<1	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		3	<1	0
Aluminum	ppm	ASTM D5185m	>25	0	<1	<1
Lead	ppm	ASTM D5185m	>100	<1	0	0
Copper	ppm	ASTM D5185m	>200	2	1	6
Tin	ppm	ASTM D5185m	>25	<1	<1	0
Antimony	ppm	ASTM D5185m	>5			
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	50	6	6	14
Barium	ppm	ASTM D5185m	15	0	0	<1
Molybdenum	ppm	ASTM D5185m	15	0	0	0
Manganese	ppm	ASTM D5185m		0	<1	1
Magnesium	ppm	ASTM D5185m	50	1	0	6
Calcium	ppm	ASTM D5185m	50	3	0	11
Phosphorus	ppm	ASTM D5185m	350	196	309	266
Zinc	ppm	ASTM D5185m	100	14	0	15
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	<1	<1	<1
Sodium	ppm	ASTM D5185m		8	<1	1
Potassium	ppm	ASTM D5185m	>20	0	<1	0
Water	%	ASTM D6304	>0.2	0.010	0.010	0.185
ppm Water	ppm	ASTM D6304	>2000	108.5	108.6	1850
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
					0.77	



## **OIL ANALYSIS REPORT**







Laboratory Sample No. Lab Number **Unique Number** 

: RP0038347 : 05979832

: 10697127

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 16 Oct 2023 Diagnosed : 18 Oct 2023

Diagnostician : Wes Davis

Test Package : IND 2 (Additional Tests: PQ) Certificate L2367

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. **OUTOKUMPU STAINLESS USA** 

HWY 43 N CALVERT, AL US 36513

Contact: MARIO JOHNSON Mario.johnson@outokumpu.com

T: (251)321-4105 F: x:

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)