


OIL ANALYSIS REPORT

FINISHING

Book Saw Outfeed Lift Table Hydraulic Unit (S/N TR110K13)

Hydraulic System

AW HYDRAULIC OIL ISO 68 (--- GAL)



Sample Rating Trend



DIAGNOSIS

Recommendation

Little or no information is provided as to the component and lubricant being tested. Recommendations are therefore generic in nature and may not apply to the current application. Please forward information as to equipment type, reservoir capacity, lubricant type and any pertinent information to allow for a more accurate assessment. Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0834762	WC0834726	WC0782939
Sample Date		Client Info		13 Oct 2023	14 Sep 2023	17 Aug 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	<1	2	2
Chromium	ppm	ASTM D5185m	>20	0	0	<1
Nickel	ppm	ASTM D5185m	>20	<1	0	0
Titanium	ppm	ASTM D5185m		0	<1	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>20	0	3	0
Lead	ppm	ASTM D5185m	>20	0	0	<1
Copper	ppm	ASTM D5185m	>20	<1	1	2
Tin	ppm	ASTM D5185m	>20	0	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	5	1	<1	<1
Barium	ppm	ASTM D5185m	5	0	0	0
Molybdenum	ppm	ASTM D5185m	5	<1	2	2
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m	25	6	11	10
Calcium	ppm	ASTM D5185m	200	83	88	89
Phosphorus	ppm	ASTM D5185m	300	297	369	369
Zinc	ppm	ASTM D5185m	370	463	444	486
Sulfur	ppm	ASTM D5185m	2500	924	1055	1027
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<1	<1	<1
Sodium	ppm	ASTM D5185m		<1	2	2
Potassium	ppm	ASTM D5185m	>20	<1	0	0
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647	>2500	305	651	338
Particles >6µm		ASTM D7647	>640	102	167	103
Particles >14μm		ASTM D7647	>80	13	25	17
Particles >21µm		ASTM D7647	>20	5	9	6
Particles >38µm		ASTM D7647	>4	0	0	1
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>18/16/13	15/14/11	17/15/12	16/14/11
FLUID DEGRADA	NOITA	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.57	0.25	0.23	0.23



OIL ANALYSIS REPORT







Laboratory Sample No. Lab Number **Unique Number**

: WC0834762 : 05980363 : 10697658

Test Package : IND 2

Certificate L2367 To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

Diagnostician

Received

Diagnosed

: 16 Oct 2023

: 17 Oct 2023

: Wes Davis

J.M. Huber Corporation PO BOX 38

CRYSTAL HILL, VA US 24539

Contact: Ted Hudson ted.hudson@huber.com T: (434)476-6628

Contact/Location: Ted Hudson - JMHCRY

F: (434)476-8133