

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

Area CONSTRUCTORS, INC Machine Id VOLVO D13 SCR 121265 Component

Hydraulic System Fluid MOBIL DTE 10 EXCEL 46 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2		
Sample Number		Client Info		SBP0004894	SBP0002273			
Sample Date		Client Info		12 Oct 2023	16 Dec 2022			
Machine Age	hrs	Client Info		10741	8525			
Oil Age	hrs	Client Info		2216	2418			
Oil Changed		Client Info		Changed	Changed			
Sample Status				NORMAL	NORMAL			
WEAR METALS		method	limit/base	current	history1	history2		
Iron	ppm	ASTM D5185m	>20	8	6			
Chromium	ppm	ASTM D5185m	>10	3	<1			
Nickel	ppm	ASTM D5185m	>10	0	0			
Titanium	ppm	ASTM D5185m		0	0			
Silver	ppm	ASTM D5185m		0	0			
Aluminum	ppm	ASTM D5185m	>10	<1	<1			
Lead	ppm	ASTM D5185m	>10	<1	<1			
Copper	ppm	ASTM D5185m	>75	1	2			
Tin	ppm	ASTM D5185m	>10	<1	0			
Vanadium	ppm	ASTM D5185m		0	0			
Cadmium	ppm	ASTM D5185m		0	0			
ADDITIVES		method	limit/base	current	history1	history2		
Boron	ppm	ASTM D5185m		0	0			
Barium	ppm	ASTM D5185m		0	0			
Molybdenum	ppm	ASTM D5185m		<1	0			
Manganese	ppm	ASTM D5185m		0	0			
Magnesium	ppm	ASTM D5185m		<1	0			
Calcium	ppm	ASTM D5185m		71	85			
Phosphorus	ppm	ASTM D5185m		456	403			
Zinc	ppm	ASTM D5185m		85	160			
Sulfur	ppm	ASTM D5185m		1744	2192			
CONTAMINANTS		method	limit/base	current	history1	history2		
Silicon	ppm	ASTM D5185m	>20	2	3			
Sodium	ppm	ASTM D5185m		3	4			
Potassium	ppm	ASTM D5185m	>20	1	0			
VISUAL		method	limit/base	current	history1	history2		
White Metal	scalar	*Visual	NONE	NONE	NONE			
Yellow Metal	scalar	*Visual	NONE	NONE	NONE			
Precipitate	scalar	*Visual	NONE	NONE	NONE			
Silt	scalar	*Visual	NONE	NONE	NONE			
Debris	scalar	*Visual	NONE	NONE	NONE			
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE			
Appearance	scalar	*Visual	NORML	NORML	NORML			
Odor	scalar	*Visual	NORML	NORML	NORML			
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG			
Free Water	scalar	*Visual		NEG	NEG			
FLUID PROPERT	IES	method	limit/base	current	history1	history2		
Visc @ 40°C	cSt	ASTM D445	45.6	40.8	41.4			
5:19:22) Rev: 1					Submitted By: Jack Linhart			



OIL ANALYSIS REPORT



c		SAMPLE IMAGE	S me	ethod	limit/base	current	history1	history2
		Color				no image	no image	no image
Oct12/23		Bottom				no image	no image	no image
0		GRAPHS						
		Ferrous Alloys						
	8	iron						
	e udd							
	4	2	17111111111111111111111111111111111111	MARAARAA AMANA	1333 Marine			
	C	9925			0ct12/23			
		ి Non-ferrous Meta	s		ŏ			
	10	copper						
	8	3						
	e	5						
	udd 4	5						
	3	3						
	-	1						
	C	Dec16/22	***************************************		0ct12/23			
		ੇ Viscosity @ 40°C			Octi			
	52	²T :						
	50	Abnormal						
	48							
	(0.0 1) 150 44	Base						
	-73 44 42							
	40	Abnormal						
	38	3						
		Dec16/22			0ct12/23			
Laboratory Sample No. Lab Number	:	WearCheck USA - 5 SBP0004894	501 Madison A Received Diagnosed	: 16 C		3	Constructor	s Inc 603659 1815 Y Street Lincoln, NE
Unique Number	r :		Diagnostician		Davis		Conto	US 68508 ct: Jack Linhart
To discuss this sample report,	cor	ntact Customer Serv					jackl@construc	torslincoln.com
* - Denotes test methods that a Statements of conformity to spec						(JCGM 106:2012		(402)434-2157 F: