

OIL ANALYSIS REPORT



GLYCOL

2010 SPARTAN 2312

Diesel Engine Fluid DIESEL ENGINE OIL SAE 15W40 (32 QTS)

DIAGNOSIS

Recommendation

We advise that you check for the source of the coolant leak. The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

Contamination

Test for glycol is positive. There is a high concentration of glycol present in the oil.


Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The oil is no longer serviceable due to the presence of contaminants.


| %2007 Feb2011 Jun2012 0∈2013 Jun2015 Mar2017 Jan2019 Jan2020 0∈2021 0∈20 | | | | | | | | | |
|--|----------|-------------|------------|--------------|-------------|--------------|--|--|--|
| SAMPLE INFORM | ATION | method | limit/base | current | history1 | history2 | | | |
| Sample Number | | Client Info | | RW0004817 | RW0003877 | RW0003935 | | | |
| Sample Date | | Client Info | | 23 Oct 2023 | 17 Feb 2023 | 01 Nov 2022 | | | |
| Machine Age | hrs | Client Info | | 8465 | 8006 | 7802 | | | |
| Oil Age | hrs | Client Info | | 459 | 204 | 143 | | | |
| Oil Changed | | Client Info | | Changed | Changed | Changed | | | |
| Sample Status | | | | SEVERE | ABNORMAL | SEVERE | | | |
| CONTAMINATION | N | method | limit/base | current | history1 | history2 | | | |
| Fuel | | WC Method | >3.0 | <1.0 | <1.0 | <1.0 | | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 | | | |
| Iron | ppm | ASTM D5185m | >90 | 11 | 5 | 5 | | | |
| Chromium | ppm | ASTM D5185m | >20 | 1 | <1 | <1 | | | |
| Nickel | ppm | ASTM D5185m | >2 | 0 | 0 | 1 | | | |
| Titanium | ppm | ASTM D5185m | >2 | 0 | 0 | 0 | | | |
| Silver | ppm | ASTM D5185m | >2 | 0 | 0 | <1 | | | |
| Aluminum | ppm | ASTM D5185m | >20 | 4 | <1 | 2 | | | |
| Lead | ppm | ASTM D5185m | >40 | 4 | 3 | 5 | | | |
| Copper | ppm | ASTM D5185m | >330 | 82 | 67 | 153 | | | |
| Tin | ppm | ASTM D5185m | >15 | <1 | 0 | <1 | | | |
| Vanadium | ppm | ASTM D5185m | | 0 | 0 | <1 | | | |
| Cadmium | ppm | ASTM D5185m | | 0 | 0 | <1 | | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 | | | |
| Boron | ppm | ASTM D5185m | 250 | <1 | 2 | 13 | | | |
| Barium | ppm | ASTM D5185m | 10 | 0 | 0 | 2 | | | |
| Molybdenum | ppm | ASTM D5185m | 100 | 209 | 102 | 179 | | | |
| Manganese | ppm | ASTM D5185m | | <1 | <1 | 1 | | | |
| Magnesium | ppm | ASTM D5185m | 450 | 869 | 857 | 301 | | | |
| Calcium | ppm | ASTM D5185m | 3000 | 997 | 1060 | 947 | | | |
| Phosphorus | ppm | ASTM D5185m | 1150 | 1044 | 953 | 787 | | | |
| Zinc | ppm | ASTM D5185m | 1350 | 1158 | 1181 | 850 | | | |
| Sulfur | ppm | ASTM D5185m | 4250 | 2837 | 3118 | 2986 | | | |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 | | | |
| Silicon | ppm | ASTM D5185m | >25 | 4 | 4 | 4 | | | |
| Sodium | ppm | ASTM D5185m | >158 | <u> </u> | 3 17 | ▲ 623 | | | |
| Potassium | ppm | ASTM D5185m | >20 | ▲ 416 | ▲ 167 | 424 | | | |
| Glycol | % | *ASTM D2982 | | 0.12 | NEG | 0.10 | | | |
| INFRA-RED | | method | limit/base | current | history1 | history2 | | | |
| Soot % | % | *ASTM D7844 | >6 | 0.1 | 0.1 | 0.1 | | | |
| Nitration | Abs/cm | *ASTM D7624 | | 12.7 | 7.5 | 9.3 | | | |
| Sulfation | Abs/.1mm | *ASTM D7415 | >30 | 21.4 | 18.7 | 19.6 | | | |
| | TION | method | limit/base | current | history1 | history2 | | | |
| FLUID DEGRADA | | mounou | | | , | | | | |
| FLUID DEGRADA Oxidation | Abs/.1mm | *ASTM D7414 | >25 | 17.4 | 14.3 | 14.4 | | | |
| | | | | | | 14.4 7.59 | | | |



OIL ANALYSIS REPORT







| VISUAL | | method | limit/base | current | history1 | history2 |
|--|-----------------------|-----------------------------------|---------------|----------------------------------|----------------------------------|--|
| White Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE | NONE |
| Precipitate | scalar | *Visual | NONE | NONE | NONE | NONE |
| Silt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE | NONE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.2 | NEG | NEG | NEG |
| Free Water | scalar | *Visual | | NEG | NEG | NEG |
| FLUID PROPERTI | ES | method | limit/base | current | history1 | history2 |
| Visc @ 100°C | cSt | ASTM D445 | 14.4 | 13.8 | 13.8 | 14.2 |
| GRAPHS | | | | | | |
| Iron (ppm) | | | 100 | Lead (ppm) | | |
| 0 - Severe | | | 80 | Severe | | |
| 0 | | | E 60 | | | |
| 0 - Abnormal | | | 40 | Abnormal | | 8 |
| ALLA . | | | 20 | | | 1. |
| | \sim | | | | 33 | 1-1 |
| May15/07 Feb17/11 Jun27/12 Oct21/13 | c1/c1nuL Mar16/17 | Jan 28/19 Jan 27/20 Oct7/21 | 0ct23/23 | May15/07 Feb17/11 Jun27/12 | 0ct21/13 Jun15/15 Mar16/17 | Jan 28/19 Jan 27/20 Oct7/21 |
| Aluminum (ppm) | | | 50 | Chromium (| ppm) | |
| 0 Severe | | | 40 | Severe | | |
| N | | | 20 | | | |
| 0 - Abnormal | | | E 20 | Abnormal | | |
| $\sim \Lambda _{1} / / /$ | 1 - | A . | 10 | | | |
| | 5 | | → 0 | L | \sim | |
| May15/07 Feb17/11 Jun27/12 Oct21/13 | c1/c1nuc Mar16/17 | Jan 28/19 Jan 27/20 Oct7/21 | 0ct23/23 | May15/07 Feb17/11 Jun27/12 | 0ct21/13 Jun15/15 Mar16/17 | Jan 28/19 Jan 27/20 0ct7/21 |
| Copper (ppm) | | , 7 | | Silicon (ppm | , _ | -, -, -, -, -, -, -, -, -, -, -, -, -, - |
| 0 Severe | | | 80 | Severe | | |
| 0 | | | 60 | | | |
| 0 | | | 톱 40 | Abnome! | | |
| • | | | 1 20 | Abnormal | | |
| | | ~~ | 0 | 1~~ | <u> </u> | |
| May15/07 Feb17/11 Jun27/12 Oct21/13 | dun 16/17 Mar16/17 | Jan 28/19 Jan 27/20 Oct7/21 | 0ct23/23 | May15/07 Feb17/11 Jun27/12 | 0ct21/13 Jun15/15 Mar16/17 | Jan 28/19 Jan 27/20 0ct7/21 |
| | Mar | Jan | Oct | | | Jan Jan |
| Viscosity @ 100°C | | | 15.0 | Base Numbe | e r Salahan panasan | |
| Abnormal 6 - | | | B/HOX | Abnormal | <u> </u> | |
| Abnormal | | | <u>و</u> 10.0 | BA | VVm | m |
| | | $\bigcirc \vee$ | 5.0 | Abnormal | | |
| Abnormal | | | | | | |
| 2- Abnormal | | | ase Mu | | | |
| 0 | Mar16/17 | Jan28/19 + | Base D | May15/07 | 0ct21/13 Jun15/15 Mar16/17 | Jan 28/19 + Jan 27/20 + Oct7/21 + |



Unique Number : 10722123 Diagnostician : Wes Davis Test Package : MOB 2 (Additional Tests: Glycol) Certificate L2367 To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

: RW0004817

: 05993763

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

Received

Diagnosed

: 30 Oct 2023

: 31 Oct 2023

Laboratory

Sample No.

Lab Number

Contact/Location: JERRY BROCK - CITFARMI

CITY OF FARMINGTON HILLS

27245 HALSTED RD

jbrock@fhgov.com

T: (248)871-2850

FARMINGTON HILLS, MI

Contact: JERRY BROCK

US 48331

F: