

OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



ELGI AC 3 (S/N MQKS030036)

Air Compressor

INGERSOLL-RAND ULTRA FG (10 GAL)

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

A decrease in the viscosity is noted. Confirmed. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Jun2019 Oct	2019 Mar2020 Aug2020	Dec2020 Aug2022 May2023 Aug20	23 Oct2023	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		USP0002894	USP0000531	USP245933
Sample Date		Client Info		25 Oct 2023	15 Aug 2023	06 May 2023
Machine Age	hrs	Client Info		11294	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	ABNORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	<1	<1
Chromium	ppm	ASTM D5185m	>4	<1	0	0
Nickel	ppm	ASTM D5185m	>4	0	0	0
Titanium	ppm	ASTM D5185m		0	<1	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>10	<1	0	0
Lead	ppm	ASTM D5185m	>20	0	0	0
Copper	ppm	ASTM D5185m	>40	<1	1	<1
Tin	ppm	ASTM D5185m	>5	0	0	0
Vanadium	ppm	ASTM D5185m		0	<1	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		20	0	8
Molybdenum	ppm	ASTM D5185m		<1	0	0
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m		0	18	9
Calcium	ppm	ASTM D5185m		0	14	46
Phosphorus	ppm	ASTM D5185m		384	219	192
Zinc	ppm	ASTM D5185m		21	166	8
Sulfur	ppm	ASTM D5185m		350	420	476
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	0	0
Sodium	ppm	ASTM D5185m		5	40	29
Potassium	ppm	ASTM D5185m	>20	0	7	4
Water	%	ASTM D6304	>0.6	0.003	0.021	0.013
ppm Water	ppm	ASTM D6304	>6000	26.2	212.2	132.4
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>20000	7037		968
Particles >6µm		ASTM D7647	>2500	1321		498
Particles >14μm		ASTM D7647	>320	61		121
Particles >21µm		ASTM D7647	>80	19		47
Particles >38μm		ASTM D7647	>20	0		2
Particles >71μm		ASTM D7647	>4	0		0
Oil Cleanliness		ISO 4406 (c)	>21/18/15	20/18/13		17/16/14
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
A adal Niconala au (ANI)	I/OII/a	ACTM DODAE		0.01	0.705	0.00

Acid Number (AN)

mg KOH/g ASTM D8045

0.725

0.21

0.62



OIL ANALYSIS REPORT



Certificate L2367

Unique Number

Test Package

: 10722770

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

: IND 2

Diagnostician

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

: Doug Bogart

US 31069

F:

Contact: JAMES EAST

T: (478)988-6048

james.east@perdue.com