


PROBLEM SUMMARY

Area ENGINE ROOM Machine Id MYCOM C02-1 (S/N 2515357 / C990480F-4) Component

Refrigeration Compressor

FRICK COMPRESSOR OIL #3 (--- PNT)

COMPONENT CONDITION SUMMARY



RECOMMENDATION

We recommend you service the filters on this component. Resample at the next service interval to monitor.

PROBLEMATIC TEST RESULTS							
Sample Status		ABNORMAL	ABNORMAL	ABNORMAL			
Particles >4µm	ASTM D7647 >20000	🔺 141589	▲ 30864	▲ 204275			
Particles >6µm	ASTM D7647 >2500	🔺 46450	5 983	4 95315			
Particles >14µm	ASTM D7647 >320	<u> </u>	63	1 704			
Oil Cleanliness	ISO 4406 (c) >21/18/	15 🔺 24/23/17	<u> </u>	a 25/24/18			


Customer Id: PERPERUSP Sample No.: USP0002906 Lab Number: 05994430 Test Package: IND 2



To manage this report scan the QR code

To discuss the diagnosis or test data: Doug Bogart +1 (800)237-1369 x4016 <u>dougb@wearcheckusa.com</u>

To change component or sample information: Customer Service +1 1-800-237-1369 <u>customerservice@wearcheck.com</u>



RECOMMENDED ACTIONS						
Action	Status	Date	Done By	Description		
Change Filter			?	We recommend you service the filters on this component.		

HISTORICAL DIAGNOSIS



13 Aug 2023 Diag: Doug Bogart

Resample at the next service interval to monitor.All component wear rates are normal. There is a high amount of silt (particulates < 14 microns in size) present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



view report

09 Apr 2023 Diag: Doug Bogart



We recommend you service the filters on this component. Resample at the next service interval to monitor.All component wear rates are normal. There is a high amount of particulates present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

30 Aug 2022 Diag: Doug Bogart

Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.









OIL ANALYSIS REPORT

Area ENGINE ROOM Machine Id MYCOM C02-1 (S/N 2515357 / C990480F-4) Component

Refrigeration Compressor

FRICK COMPRESSOR OIL #3 (--- PNT)

DIAGNOSIS

Recommendation

We recommend you service the filters on this component. Resample at the next service interval to monitor.

Wear


All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.





SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		USP0002906	USP245919	USP218708
Sample Date		Client Info		25 Oct 2023	13 Aug 2023	09 Apr 2023
Machine Age	hrs	Client Info		39698	38175	36621
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>8	2	<1	2
Chromium	ppm	ASTM D5185m	>2	<1	0	0
Nickel	ppm	ASTM D5185m		0	0	0
Titanium	ppm	ASTM D5185m		<1	<1	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>3	0	0	0
Lead	ppm	ASTM D5185m	>2	0	0	0
Copper	ppm	ASTM D5185m		<1	<1	0
Tin	ppm	ASTM D5185m		<1	0	0
Vanadium	ppm	ASTM D5185m		<1	<1	0
Cadmium	ppm	ASTM D5185m		<1	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m		0	0	0
Calcium	ppm	ASTM D5185m		0	0	0
Phosphorus	ppm	ASTM D5185m		0	0	0
Zinc	ppm	ASTM D5185m		0	0	0
Sulfur	ppm	ASTM D5185m		12	0	0
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m		<1	0	0
Sodium	ppm	ASTM D5185m	210	1	<1	<1
Potassium	ppm	ASTM D5185m	>20	<1	0	0
Water	%	ASTM D6304		0.002	0.003	0.002
ppm Water	ppm	ASTM D6304		16.3	32.5	15.9
FLUID CLEANLIN		method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>20000	▲ 141589	▲ 30864	▲ 204275
Particles >6µm		ASTM D7647	>2500	46450	▲ 5983	▲ 95315
Particles >14µm		ASTM D7647	>320	▲ 713	63	▲ 1704
Particles >21µm		ASTM D7647		60	8	▲ 138
Particles >38µm		ASTM D7647	>20	0	1	2
Particles >71µm		ASTM D7647		0	0	0
Oil Cleanliness		ISO 4406 (c)	>21/18/15	▲ 24/23/17	▲ 22/20/13	▲ 25/24/18
FLUID DEGRADA		method	limit/base		historyd	history2
I LOID DEGLINDA		methou	iiiiii/base	current	history1	TISLUTYZ



OIL ANALYSIS REPORT








VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	LIGHT
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.01	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	73	68.7	68.6	69.6
SAMPLE IMAGES	S	method	limit/base	current	history1	history2
Color						

Bottom



Contact/Location: JAMES EAST - PERPERUSP