

# **OIL ANALYSIS REPORT**

## Sample Rating Trend



HOWDEN C4 - PFG (S/N MK5-087)

**Refrigeration Compressor** 

SR 2033 (--- GAL)

### Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the

## Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

A <sub>pri</sub> 2018 A <sub>pri</sub> 2019 A <sub>pri</sub> 2020 A <sub>pri</sub> 2021 Jani2022 0:e2022 0:e2023						
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0832880	WC0746948	WC0700813
Sample Date		Client Info		25 Oct 2023	18 Jun 2023	18 Oct 2022
Machine Age	hrs	Client Info		93648	90450	85092
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>8	5	5	<1
Chromium	ppm	ASTM D5185m	>2	<1	0	0
Nickel	ppm	ASTM D5185m		0	0	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>3	0	0	2
Lead	ppm	ASTM D5185m	>2	0	0	0
Copper	ppm	ASTM D5185m	>8	<1	0	0
Tin	ppm	ASTM D5185m	>4	<1	0	0
Vanadium	ppm	ASTM D5185m		<1	0	<1
Cadmium	ppm	ASTM D5185m		<1	<1	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		0	0	0
Calcium	ppm	ASTM D5185m		0	0	0
Phosphorus	ppm	ASTM D5185m		1	<1	5
Zinc	ppm	ASTM D5185m		0	0	0
Sulfur	ppm	ASTM D5185m		12	12	0
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<1	0	0
Sodium	ppm	ASTM D5185m		1	0	0
Potassium	ppm	ASTM D5185m	>20	<1	0	0
Water	%	ASTM D6304	>0.01	0.00	0.003	0.001
ppm Water	ppm	ASTM D6304	>100	0.00	29.7	7.6
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2

0.015


Acid Number (AN) mg KOH/g ASTM D974

0.013

0.015



# **OIL ANALYSIS REPORT**



	١
	`
	F
	9
 	9
0ct25/23	,
Oct	(
	E
	F

VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	LIGHT
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.01	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG

Wate	er (KF)					
5000				· \		
E 4000				/\		
4000 mater 3000 - 30000 - 3000 - 3000 - 3000 - 3000 - 3000 - 3000 - 3000 - 3000 - 3000				/ \		
1000				/ \	ļļ	
O BOWSE	mal					
Apr11/18	Apr9/19	Apr14/20	Apr20/21	Jan10/22	Oct18/22	0ct25/23

FLUID PROPE	RTIES	method			
Visc @ 40°C	cSt	ASTM D445	62.4	62.8	62.8


SAMPLE IMAGES

Color











**Bottom** 





















Certificate L2367

Laboratory Sample No. Lab Number **Unique Number** Test Package : IND 2

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : WC0832880 : 05994470 : 10722830

Received Diagnosed Diagnostician : Doug Bogart

: 31 Oct 2023 : 01 Nov 2023 SOUTHEASTERN REFRIGERATION

310 26TH AVE. WEST BIRMINGHAM, AL US 35204

Contact: GREGG KING gregg@serfco.com

T: (205)322-6587 F: (205)322-6580

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)