

### **OIL ANALYSIS REPORT**

#### Sample Rating Trend


## NORMAL



# CATERPILLAR D6 LGP 10040 (S/N KEW01159)

Right Final Drive

NOT GIVEN (--- GAL)





#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil


#### **Fluid Condition**

The condition of the oil is acceptable for the time in service.

			Sep.2023	Oct2023		
SAMPLE INFORI	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0862930	WC0831295	
Sample Date		Client Info		24 Oct 2023	12 Sep 2023	
Machine Age	hrs	Client Info		1270	721	
Oil Age	hrs	Client Info		549	721	
Oil Changed		Client Info		Changed	Changed	
Sample Status				NORMAL	NORMAL	
WEAR METALS		method	limit/base	current	history1	history2
ron	ppm	ASTM D5185m	>800	8	35	
Chromium	ppm	ASTM D5185m	>10	0	<1	
Nickel	ppm	ASTM D5185m	>5	0	0	
Titanium	ppm	ASTM D5185m	>15	0	<1	
Silver	ppm	ASTM D5185m	>2	0	0	
Aluminum	ppm	ASTM D5185m	>75	<1	2	
_ead	ppm	ASTM D5185m	>10	0	<1	
Copper	ppm	ASTM D5185m		1	2	
Tin	ppm	ASTM D5185m	>8	0	<1	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		154	116	
Barium	ppm	ASTM D5185m		0	0	
Molybdenum	ppm	ASTM D5185m		0	0	
Manganese	ppm	ASTM D5185m		<1	2	
Magnesium	ppm	ASTM D5185m		13	3	
Calcium	ppm	ASTM D5185m		110	385	
Phosphorus	ppm	ASTM D5185m		337	359	
Zinc	ppm	ASTM D5185m		19	34	
Sulfur	ppm	ASTM D5185m		2878	15134	
CONTAMINANTS	S	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>400	2	3	
Sodium	ppm	ASTM D5185m		2	4	
Potassium	ppm	ASTM D5185m	>20	- <1	1	
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	NONE	NONE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	
Free Water	scalar	*Visual		NEG	NEG	
FLUID PROPER	TIES	method	limit/base	current	history1	history2
LOID FILOI LIT		111011100	- IIIIIII Dasc	Garron	1113101 y 1	- 113toi y 2




### **OIL ANALYSIS REPORT**






#### **GRAPHS**



#### Non-ferrous Metals



# 300 250 cSt (40°C) 150





Certificate L2367

Laboratory Sample No. Lab Number Unique Number : 10723006 Test Package : CONST

: WC0862930 : 05994646

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 31 Oct 2023 Diagnosed : 01 Nov 2023

Diagnostician : Don Baldridge

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

TRADER CONSTRUCTION CO.

PO DRAWER 1578 NEW BERN, NC US 28563

F: (252)638-4871

Contact: MIKE WYATT

mwyatt@traderconstruction.com T: (252)633-1399

Contact/Location: MIKE WYATT - TRANEW