



OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Area
KANSAS/44/EG - SKID STEER
 Machine Id
53.181L [KANSAS^44^EG - SKID STEER]
 Component
Left Chain Case
 Fluid
DIESEL ENGINE OIL SAE 15W40 (--- GAL)



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		WC0862649	---	---
Sample Date	Client Info		23 Oct 2023	---	---
Machine Age	hrs	Client Info	254	---	---
Oil Age	hrs	Client Info	254	---	---
Oil Changed	Client Info		Not Chngd	---	---
Sample Status			NORMAL	---	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >632	70	---	---
Chromium	ppm	ASTM D5185m >3	<1	---	---
Nickel	ppm	ASTM D5185m >3	<1	---	---
Titanium	ppm	ASTM D5185m	<1	---	---
Silver	ppm	ASTM D5185m	0	---	---
Aluminum	ppm	ASTM D5185m >19	2	---	---
Lead	ppm	ASTM D5185m >6	1	---	---
Copper	ppm	ASTM D5185m >46	1	---	---
Tin	ppm	ASTM D5185m >3	<1	---	---
Vanadium	ppm	ASTM D5185m	<1	---	---
Cadmium	ppm	ASTM D5185m	0	---	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 250	66	---	---
Barium	ppm	ASTM D5185m 10	58	---	---
Molybdenum	ppm	ASTM D5185m 100	36	---	---
Manganese	ppm	ASTM D5185m	2	---	---
Magnesium	ppm	ASTM D5185m 450	486	---	---
Calcium	ppm	ASTM D5185m 3000	1509	---	---
Phosphorus	ppm	ASTM D5185m 1150	956	---	---
Zinc	ppm	ASTM D5185m 1350	1117	---	---
Sulfur	ppm	ASTM D5185m 4250	3134	---	---

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >82	41	---	---
Sodium	ppm	ASTM D5185m >158	5	---	---
Potassium	ppm	ASTM D5185m >20	5	---	---

VISUAL


	method	limit/base	current	history1	history2
White Metal	scalar	*Visual NONE	NONE	---	---
Yellow Metal	scalar	*Visual NONE	NONE	---	---
Precipitate	scalar	*Visual NONE	NONE	---	---
Silt	scalar	*Visual NONE	MODER	---	---
Debris	scalar	*Visual NONE	NONE	---	---
Sand/Dirt	scalar	*Visual NONE	NONE	---	---
Appearance	scalar	*Visual NORML	NORML	---	---
Odor	scalar	*Visual NORML	NORML	---	---
Emulsified Water	scalar	*Visual >0.2	NEG	---	---
Free Water	scalar	*Visual	NEG	---	---

FLUID PROPERTIES

	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445 115	75.2	---	---






OIL ANALYSIS REPORT



SAMPLE IMAGES	method	limit/base	current	history1	history2
Color			no image	no image	no image
Bottom			no image	no image	no image

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0862649 **Received** : 31 Oct 2023
Lab Number : 05994801 **Diagnosed** : 02 Nov 2023
Unique Number : 10723161 **Diagnostician** : Don Baldrige
Test Package : CONST

SHERWOOD CONSTRUCTION CO INC
 3219 WEST MAY ST
 WICHITA, KS
 US 67213
 Contact: BILL ORCUTT
 william.orcutt@wildcat.net
 T:
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)