

OIL ANALYSIS REPORT

NFDM [1857683] PT11PP03BB01

Component

Bearing Fluid

MOBIL SHC 626 (--- GAL)

Sample Rating Trend

NORMAL

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition

The condition of the oil is acceptable for the time in service.

| | | | | Oct2023 | | |
|------------------|--------|-------------|------------|-------------|----------|----------|
| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | WC0864040 | | |
| Sample Date | | Client Info | | 25 Oct 2023 | | |
| Machine Age | hrs | Client Info | | 0 | | |
| Oil Age | hrs | Client Info | | 0 | | |
| Oil Changed | | Client Info | | N/A | | |
| Sample Status | | | | NORMAL | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >20 | 0 | | |
| Chromium | ppm | ASTM D5185m | >20 | 0 | | |
| Nickel | ppm | ASTM D5185m | >20 | 0 | | |
| Titanium | ppm | ASTM D5185m | | 0 | | |
| Silver | ppm | ASTM D5185m | | 0 | | |
| Aluminum | ppm | ASTM D5185m | >20 | 0 | | |
| Lead | ppm | ASTM D5185m | >20 | 0 | | |
| Copper | ppm | ASTM D5185m | >20 | 0 | | |
| Tin | ppm | ASTM D5185m | >20 | 0 | | |
| Vanadium | ppm | ASTM D5185m | | 0 | | |
| Cadmium | ppm | ASTM D5185m | | 0 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 0 | | |
| Barium | ppm | ASTM D5185m | | <1 | | |
| Molybdenum | ppm | ASTM D5185m | | 0 | | |
| Manganese | ppm | ASTM D5185m | | 0 | | |
| Magnesium | ppm | ASTM D5185m | | <1 | | |
| Calcium | ppm | ASTM D5185m | | 2 | | |
| Phosphorus | ppm | ASTM D5185m | | 443 | | |
| Zinc | ppm | ASTM D5185m | | 3 | | |
| Sulfur | ppm | ASTM D5185m | | 41 | | |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >15 | 0 | | |
| Sodium | ppm | ASTM D5185m | 7.0 | 0 | | |
| Potassium | ppm | ASTM D5185m | >20 | 0 | | |
| VISUAL | | method | limit/base | current | history1 | history2 |
| White Metal | scalar | *Visual | NONE | NONE | | |
| Yellow Metal | scalar | *Visual | NONE | NONE | | |
| Precipitate | scalar | *Visual | NONE | NONE | | |
| Silt | scalar | *Visual | NONE | NONE | | |
| Debris | scalar | *Visual | NONE | NONE | | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | | |
| Appearance | scalar | *Visual | NORML | NORML | | |
| Odor | scalar | *Visual | NORML | NORML | | |
| Emulsified Water | scalar | *Visual | >2 | NEG | | |
| Free Water | scalar | *Visual | | NEG | | |
| FLUID PROPERT | | method | limit/base | current | history1 | history2 |





OIL ANALYSIS REPORT





GRAPHS





Viscosity @ 40°C







Certificate L2367

Laboratory Sample No. Lab Number

Unique Number : 10724471 Test Package : IND 1

: WC0864040 : 05996111

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 01 Nov 2023 Diagnosed : 03 Nov 2023 Diagnostician : Don Baldridge

LEPRINO FOODS-GREELEY

1302 1ST AVE GREELEY, CO US 80631-5909

Contact: ERIC KLINE EKLINE@LEPRINOFOODS.COM

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: (970)347-5190