




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area
PQ
 Machine Id
2014 KENWORTH 3709

Component
Diesel Engine
 Fluid
CHEVRON DELO 400 XLE 10W30 (44 QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		WC0625662	WCMFC23115	WCMFB85296
Sample Date	Client Info		20 Oct 2023	20 Apr 2020	07 Mar 2019
Machine Age	mls	Client Info	432606	342154	313901
Oil Age	mls	Client Info	52000	0	0
Oil Changed	Client Info		Changed	Not Changd	N/A
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	<1.0	<1.0
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	59	23	16
Chromium	ppm	ASTM D5185m >20	2	<1	<1
Nickel	ppm	ASTM D5185m >4	<1	<1	<1
Titanium	ppm	ASTM D5185m	<1	0	<1
Silver	ppm	ASTM D5185m >3	0	0	0
Aluminum	ppm	ASTM D5185m >20	14	8	7
Lead	ppm	ASTM D5185m >40	1	<1	1
Copper	ppm	ASTM D5185m >330	4	5	5
Tin	ppm	ASTM D5185m >15	<1	<1	0
Antimony	ppm	ASTM D5185m	---	0	2
Vanadium	ppm	ASTM D5185m	<1	0	0
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	16	18	24
Barium	ppm	ASTM D5185m	0	0	<1
Molybdenum	ppm	ASTM D5185m	19	23	13
Manganese	ppm	ASTM D5185m	<1	<1	<1
Magnesium	ppm	ASTM D5185m	657	613	624
Calcium	ppm	ASTM D5185m 2900	1342	1321	1389
Phosphorus	ppm	ASTM D5185m 1100	708	682	663
Zinc	ppm	ASTM D5185m 1200	825	742	785
Sulfur	ppm	ASTM D5185m 4000	2747	3106	2515

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	8	6	6
Sodium	ppm	ASTM D5185m	24	3	3
Potassium	ppm	ASTM D5185m >20	7	9	6

INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	1.1	0.9	0.7
Nitration	Abs/cm	*ASTM D7624 >20	12.4	11.6	10.7
Sulfation	Abs/.1mm	*ASTM D7415 >30	26.3	25.2	23.1

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	21.2	18.7	16.7
Base Number (BN)	mg KOH/g	ASTM D2896 10.3	5.8	5.4	5.7











OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	11.9	11.5	11.5

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0625662
Lab Number : 05997226
Unique Number : 10725586
Test Package : MOB1+

LTI/MILKY WAY - MOUNT VERNON
 3814 OLD HWY 99 S RD
 MOUNT VERNON, WA
 US 98273
 Contact: JOHN VAN WINGERDEN
 jvw@lynden.com
 T: (360)354-2101
 F: (360)354-3571

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)