




OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id
8433942 (S/N 1932)
 Component
Compressor
 Fluid
KAESER SIGMA (OEM) S-460 (--- GAL)

DIAGNOSIS

Recommendation
 Resample at the next service interval to monitor.

Wear
 All component wear rates are normal.

Contamination
 The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.

Fluid Condition
 The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			KC125947	KC106696	---
Sample Date	Client Info			27 Oct 2023	17 Nov 2022	---
Machine Age	hrs	Client Info		7042	2898	---
Oil Age	hrs	Client Info		0	2898	---
Oil Changed	Client Info			N/A	Not Changd	---
Sample Status				NORMAL	ABNORMAL	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	<1	---
Chromium	ppm	ASTM D5185m	>10	0	0	---
Nickel	ppm	ASTM D5185m	>3	0	5	---
Titanium	ppm	ASTM D5185m	>3	0	0	---
Silver	ppm	ASTM D5185m	>2	0	<1	---
Aluminum	ppm	ASTM D5185m	>10	0	2	---
Lead	ppm	ASTM D5185m	>10	0	3	---
Copper	ppm	ASTM D5185m	>50	<1	6	---
Tin	ppm	ASTM D5185m	>10	<1	<1	---
Vanadium	ppm	ASTM D5185m		0	<1	---
Cadmium	ppm	ASTM D5185m		0	0	---






ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	---
Barium	ppm	ASTM D5185m	90	72	<1	---
Molybdenum	ppm	ASTM D5185m		0	<1	---
Manganese	ppm	ASTM D5185m		0	0	---
Magnesium	ppm	ASTM D5185m	90	69	6	---
Calcium	ppm	ASTM D5185m	2	4	2	---
Phosphorus	ppm	ASTM D5185m		46	271	---
Zinc	ppm	ASTM D5185m		55	321	---

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	2	---
Sodium	ppm	ASTM D5185m		5	4	---
Potassium	ppm	ASTM D5185m	>20	0	4	---
Water	%	ASTM D6304	>0.05	0.013	0.004	---
ppm Water	ppm	ASTM D6304	>500	131.5	46.6	---

FLUID CLEANLINESS		method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		3468	14200	---
Particles >6µm		ASTM D7647	>1300	1072	▲ 4369	---
Particles >14µm		ASTM D7647	>80	59	▲ 417	---
Particles >21µm		ASTM D7647	>20	12	▲ 108	---
Particles >38µm		ASTM D7647	>4	1	▲ 13	---
Particles >71µm		ASTM D7647	>3	0	2	---
Oil Cleanliness		ISO 4406 (c)	>--/17/13	19/17/13	▲ 21/19/16	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.4	0.32	0.60	---


OIL ANALYSIS REPORT








VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	VLITE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	46	44.2	46.0

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------



GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : KC125947
Lab Number : 05997987
Unique Number : 10726347
Test Package : IND 2

LAB CORP DRUG DEVELOPMENT INC
 100 MEHLERS RD
 SOMERSET, NJ
 US 08873
 Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: