




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**FORD 3335**

Component  
**Diesel Engine**

Fluid  
**DIESEL ENGINE OIL SAE 15W40 (5 GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>WC0694249</b>	WC0620340	WC0576794
Sample Date	Client Info			<b>20 Oct 2023</b>	25 Sep 2021	03 May 2021
Machine Age	mls	Client Info		<b>309800</b>	261275	251525
Oil Age	mls	Client Info		<b>0</b>	7000	7000
Oil Changed	Client Info			<b>N/A</b>	Changed	Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method			<b>NEG</b>	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	<b>7</b>	25	27
Chromium	ppm	ASTM D5185m	>20	<b>0</b>	2	2
Nickel	ppm	ASTM D5185m	>2	<b>0</b>	0	0
Titanium	ppm	ASTM D5185m	>2	<b>0</b>	0	<1
Silver	ppm	ASTM D5185m	>2	<b>0</b>	0	<1
Aluminum	ppm	ASTM D5185m	>25	<b>0</b>	2	2
Lead	ppm	ASTM D5185m	>40	<b>0</b>	2	1
Copper	ppm	ASTM D5185m	>330	<b>0</b>	1	1
Tin	ppm	ASTM D5185m	>15	<b>0</b>	<1	<1
Antimony	ppm	ASTM D5185m		<b>---</b>	<1	0
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m		<b>0</b>	0	0

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	250	<b>18</b>	6	11
Barium	ppm	ASTM D5185m	10	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	100	<b>61</b>	66	62
Manganese	ppm	ASTM D5185m		<b>0</b>	<1	<1
Magnesium	ppm	ASTM D5185m	450	<b>800</b>	957	925
Calcium	ppm	ASTM D5185m	3000	<b>1217</b>	1154	1249
Phosphorus	ppm	ASTM D5185m	1150	<b>984</b>	1022	1085
Zinc	ppm	ASTM D5185m	1350	<b>1206</b>	1271	1271
Sulfur	ppm	ASTM D5185m	4250	<b>3120</b>	2752	2775



CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<b>3</b>	3	4
Sodium	ppm	ASTM D5185m	>158	<b>2</b>	3	2
Potassium	ppm	ASTM D5185m	>20	<b>0</b>	0	<1

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	<b>0.2</b>	0.3	0.4
Nitration	Abs/cm	*ASTM D7624	>20	<b>7.3</b>	11.3	13.8
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>18.5</b>	22	25.2

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>14.6</b>	19.5	25.6
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	<b>8.8</b>	---	---











# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	14.4	<b>13.3</b>	13.4	13.2

### GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : WC0694249 **Received** : 06 Nov 2023  
**Lab Number** : 05998686 **Diagnosed** : 06 Nov 2023  
**Unique Number** : 10727046 **Diagnostician** : Wes Davis  
**Test Package** : MOB 1 ( Additional Tests: TBN )

**INTERSTATE WASTE-CHESTER**  
 89 BLACK MEADOW RD  
 CHESTER, NY  
 US 10918  
 Contact: ROB CLARKE  
 rclarke@interstatewaste.com  
 T:  
 F: (845)572-3301

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)