

## **PROBLEM SUMMARY**

Sample Rating Trend

VIS DEBRIS

Machine Id

# KAESER BSD 50 5012170 (S/N 1172)

Component

Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

COMPONENT CONDITION SUMMARY

No relevant graphs to display

#### RECOMMENDATION

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.

| PROBLEMATIC TEST RESULTS |        |         |      |          |        |          |
|--------------------------|--------|---------|------|----------|--------|----------|
| Sample Status            |        |         |      | ABNORMAL | NORMAL | ABNORMAL |
| Debris                   | scalar | *Visual | NONE | ▲ MODER  | VLITE  | ▲ HEAVY  |

Customer Id: KLIDEC Sample No.: KCPA007998 Lab Number: 05999853 Test Package: IND 2

To manage this report scan the QR code

To discuss the diagnosis or test data:

Don Baldridge +1 don.b505@comcast.net

To change component or sample information: Customer Service +1 1-800-237-1369 customerservice@wearcheck.com

#### **RECOMMENDED ACTIONS**

| Action | Status | Date | Done By | Description   |
|--------|--------|------|---------|---|
| Alert  |        |      | ?       | We were unable to perform a particle count due to a high concentration of particles present in this sample. |

#### HISTORICAL DIAGNOSIS

#### 26 Oct 2022 Diag: Doug Bogart

#### NORMAL



No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable. The AN level is acceptable for this fluid.

# View report

#### 21 Mar 2022 Diag: Jonathan Hester

#### VIS DEBRIS



No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample. All component wear rates are normal. High concentration of visible dirt/debris present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

# view report

#### 18 May 2021 Diag: Don Baldridge

#### VIS DEBRIS




No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample. All component wear rates are normal. Moderate concentration of visible dirt/debris present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.





## **OIL ANALYSIS REPORT**

Sample Rating Trend



## KAESER BSD 50 5012170 (S/N 1172)

Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

#### **DIAGNOSIS**

#### Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.

#### Wear

All component wear rates are normal.

#### Contamination

Moderate concentration of visible dirt/debris present in the oil.

#### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

|                 |        | Jan 2015     | Oct2016 Jan2018 | Jun2019 Mar2022 | Oct2023     |             |
|-----------------|--------|--------------|-----------------|-----------------|-------------|-------------|
| SAMPLE INFORM   | MATION | method       | limit/base      | current         | history1    | history2    |
| Sample Number   |        | Client Info  |                 | KCPA007998      | KCP38429    | KCP43359    |
| Sample Date     |        | Client Info  |                 | 30 Oct 2023     | 26 Oct 2022 | 21 Mar 2022 |
| Machine Age     | hrs    | Client Info  |                 | 62893           | 55360       | 50860       |
| Oil Age         | hrs    | Client Info  |                 | 0               | 4500        | 6889        |
| Oil Changed     |        | Client Info  |                 | N/A             | Changed     | Changed     |
| Sample Status   |        |              |                 | ABNORMAL        | NORMAL      | ABNORMAL    |
| WEAR METALS     |        | method       | limit/base      | current         | history1    | history2    |
| Iron            | ppm    | ASTM D5185m  | >50             | 0               | 0           | 0           |
| Chromium        | ppm    | ASTM D5185m  | >10             | 0               | 0           | 0           |
| Nickel          | ppm    | ASTM D5185m  | >3              | 0               | 0           | <1          |
| Titanium        | ppm    | ASTM D5185m  | >3              | 0               | 0           | 0           |
| Silver          | ppm    | ASTM D5185m  | >2              | 0               | 0           | <1          |
| Aluminum        | ppm    | ASTM D5185m  | >10             | 0               | 0           | <1          |
| Lead            | ppm    | ASTM D5185m  | >10             | 0               | 0           | 0           |
| Copper          | ppm    | ASTM D5185m  | >50             | 9               | 12          | 10          |
| Tin             | ppm    | ASTM D5185m  | >10             | 0               | 0           | <1          |
| Antimony        | ppm    | ASTM D5185m  |                 |                 |             |             |
| Vanadium        | ppm    | ASTM D5185m  |                 | 0               | 0           | 0           |
| Cadmium         | ppm    | ASTM D5185m  |                 | 0               | 0           | 0           |
| ADDITIVES       |        | method       | limit/base      | current         | history1    | history2    |
| Boron           | ppm    | ASTM D5185m  | 0               | 0               | 0           | 0           |
| Barium          | ppm    | ASTM D5185m  | 90              | 0               | 0           | 0           |
| Molybdenum      | ppm    | ASTM D5185m  | 0               | 0               | 0           | 0           |
| Manganese       | ppm    | ASTM D5185m  |                 | 0               | 0           | 0           |
| Magnesium       | ppm    | ASTM D5185m  | 100             | <1              | 0           | 7           |
| Calcium         | ppm    | ASTM D5185m  | 0               | 0               | 0           | 0           |
| Phosphorus      | ppm    | ASTM D5185m  | 0               | <1              | <1          | 7           |
| Zinc            | ppm    | ASTM D5185m  | 0               | 0               | 0           | 0           |
| Sulfur          | ppm    | ASTM D5185m  | 23500           | 18341           | 21752       | 15708       |
| CONTAMINANTS    | }      | method       | limit/base      | current         | history1    | history2    |
| Silicon         | ppm    | ASTM D5185m  | >25             | 0               | <1          | <1          |
| Sodium          | ppm    | ASTM D5185m  |                 | 1               | <1          | 1           |
| Potassium       | ppm    | ASTM D5185m  | >20             | 0               | 0           | 0           |
| Water           | %      | ASTM D6304   |                 | 0.010           | 0.012       | 0.013       |
| ppm Water       | ppm    | ASTM D6304   | >500            | 103.0           | 123.9       | 133.4       |
| FLUID CLEANLIN  | IESS   | method       | limit/base      | current         | history1    | history2    |
| Particles >4μm  |        | ASTM D7647   |                 |                 | 1623        |             |
| Particles >6µm  |        | ASTM D7647   | >1300           |                 | 380         |             |
| Particles >14μm |        | ASTM D7647   | >80             |                 | 55          |             |
| Particles >21µm |        | ASTM D7647   | >20             |                 | 18          |             |
| Particles >38μm |        | ASTM D7647   | >4              |                 | 3           |             |
| Particles >71μm |        | ASTM D7647   | >3              |                 | 0           |             |
| Oil Cleanliness |        | ISO 4406 (c) | >/17/13         |                 | 18/16/13    |             |
| FLUID DEGRADA   | ATION  | method       | limit/base      | current         | history1    | history2    |
|                 | 1/011/ | 10T11 D0015  | 4.0             |                 | 0.40        |             |



### **OIL ANALYSIS REPORT**







Laboratory Sample No. Lab Number **Unique Number** 

: KCPA007998 : 05999853 : 10728213

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received Diagnosed

: 06 Nov 2023 : 08 Nov 2023

Diagnostician : Don Baldridge

Test Package : IND 2 ( Additional Tests: KF, PrtCount ) Certificate L2367 To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

KLIKLOK CORP 5224 SNAPFINGER WOODS DR

DECATUR, GA US 30035

Contact: JEREMY WILSON jeremy.wilson@syntegon.com

T:

F: